

## ANNA-50-7-S

~15° spot beam with 7 optics

### SPECIFICATION:

Dimensions	Ø 50.0 mm
Height	10.7 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ




### MATERIALS:

Component	Type	Material	Colour	Finish
ANNA-50-7-S	Multi-lens	PMMA	clear	

### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C11670_ANNA-50-7-S » Box size: 480 x 280 x 300 mm	512	96	32	7.5




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### OPTICAL RESULTS (MEASURED):


##### LUMILEDS

LED LUXEON A  
 FWHM / FWTM 19.0° / 40.0°  
 Efficiency 87 %  
 Peak intensity 5.7 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### LUMILEDS

LED LUXEON Rebel  
 FWHM / FWTM 13.0° / 28.0°  
 Efficiency 92 %  
 Peak intensity 9.3 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:



##### LUMILEDS



LED LUXEON Rebel ES  
 FWHM / FWTM 18.0° / 36.0°  
 Efficiency 93 %  
 Peak intensity 6.1 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:



##### NICHIA

LED NCSxx19A  
 FWHM / FWTM 16.0° / 35.0°  
 Efficiency 91 %  
 Peak intensity 6.7 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:


#### OPTICAL RESULTS (MEASURED):

<p><b>NICHIA</b></p> <p>LED NVSxx19A            FWHM / FWTM 19.0° / 42.0°            Efficiency 91 %            Peak intensity 4.9 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED OSLON SSL 150            FWHM / FWTM 12.0° / 22.0°            Efficiency 90 %            Peak intensity 13.7 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p> 
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED OSLON SSL 80            FWHM / FWTM 11.0° / 26.0°            Efficiency 90 %            Peak intensity 11.7 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	


#### OPTICAL RESULTS (SIMULATED):




LED XB-H  
 FWHM / FWTM 16.0° / 30.0°  
 Efficiency 94 %  
 Peak intensity 8.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED LUXEON CZ  
 FWHM / FWTM 28.0° / 55.0°  
 Efficiency 96 %  
 Peak intensity 3.5 cd/lm  
 LEDs/each optic 1  
 Light colour Red  
 Required components:



LED NVSxx19B/NVSxx19C  
 FWHM / FWTM 18.0° / 34.0°  
 Efficiency 95 %  
 Peak intensity 6.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED Double Dome (GM2BB)  
 FWHM / FWTM 12.0°  
 Efficiency %  
 LEDs/each optic 1  
 Light colour White  
 Required components:

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)