

## EMILY-M2

~30° medium beam. 14.88 mm high lens.

### SPECIFICATION:

Dimensions	Ø 26.0
Height	14.9 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




### MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
EMILY-M2	Single lens	PMMA	clear		
SPUTNIK-TAPE	Tape	Acryl tape	black		

### ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA11391_EMILY-M2	Single lens	1690	260	130	10.6
» Box size: 480 x 280 x 300 mm					





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):



LED XB-H  
FWHM / FWTM 30.0° / 47.0°  
Efficiency 89 %  
Peak intensity 3.3 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED XP-E  
FWHM / FWTM 29.0° / 47.0°  
Efficiency 92 %  
Peak intensity 3.2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files



LED XP-G  
FWHM / FWTM 29.0° / 44.0°  
Efficiency 92 %  
Peak intensity 3.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files

## OPTICAL RESULTS (MEASURED):



LED LUXEON Rebel  
FWHM / FWTM 28.0°  
Efficiency 87 %  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files



LED NCSxx19A  
FWHM / FWTM 30.0°  
Efficiency 88 %  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files




LED NVSxx19A  
FWHM / FWTM 28.0° / 48.0°  
Efficiency 88 %  
Peak intensity 2.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files

### OPTICAL RESULTS (MEASURED):

**OSRAM**  
Opto Semiconductors

LED OSLON Square EC  
FWHM / FWTM 30.0° / 47.0°  
Efficiency 89 %  
Peak intensity 3.3 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED OSLON SSL 150  
FWHM / FWTM 30.0°  
Efficiency %  
LEDs/each optic 1  
Light colour/type White  
Required components:


Light distribution files

**OSRAM**  
Opto Semiconductors

LED OSLON SSL 80  
FWHM / FWTM 28.0°  
Efficiency 85 %  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files

## OPTICAL RESULTS (MEASURED):

  
SEUL SEMICONDUCTOR

LED	Z5
FWHM / FWTM	28.0°
Efficiency	%
LEDs/each optic	1
Light colour/type	White

Required components:

Light distribution files

**SHARP**

LED	Double Dome (GM2BB)
FWHM / FWTM	28.0°
Efficiency	%
LEDs/each optic	1
Light colour/type	White


Required components:

Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED XP-E  
FWHM / FWTM 31.0° / 48.0°  
Efficiency 93 %  
Peak intensity 3.4 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED NCSxx19B  
FWHM / FWTM 28.0°  
Efficiency 89 %  
Peak intensity 2.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED NVSxE21A  
FWHM / FWTM 32.0° / 61.0°  
Efficiency 92 %  
Peak intensity 2.3 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:




Light distribution files

### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors



LED OSCONIQ P 3030  
FWHM / FWTM 31.0° / 49.0°  
Efficiency 96 %  
Peak intensity 3.3 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED OSLON Square CSSRM2/CSSRM3  
FWHM / FWTM 30.0° / 49.0°  
Efficiency 94 %  
Peak intensity 3.4 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**SAMSUNG**

LED LH351B  
FWHM / FWTM 30.0° / 50.0°  
Efficiency 93 %  
Peak intensity 3.2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files



### OPTICAL RESULTS (SIMULATED):

#### SAMSUNG

LED	LM28xB Series
FWHM / FWTM	29.0° / 50.0°
Efficiency	94 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)