

GABRIELLA-45-W

~35° wide beam with holder and installation tape

SPECIFICATION:

Dimensions	Ø 45.0
Height	29.2 mm
Fastening	tape, pin, screw
ROHS compliant	yes ⓘ

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
GABRIELLA-45-W	Single lens	PMMA	clear		
GABRIELLA-45-HLD-T	Holder	PC	black		
GABRIELLA-TAPE	Tape	Acryl tape	black		


ORDERING INFORMATION:

Quantities for one set:

Single lens	1
Assembly	1



Component		Qty in box	MOQ	MPQ	Box weight (kg)
C15813_GABRIELLA-45-W » Box size: 476 x 273 x 292 mm	Single lens	405	90	45	8.6
CA15928_GABRIELLA-45-HLD-T » Box size: 476 x 273 x 292 mm	Assembly	405	90	45	5.7





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED XM-L RGBW (XMLCTW)
 FWHM / FWTM 36.0° / 62.0°
 Efficiency 79 %
 Peak intensity 1.8 cd/lm
 LEDs/each optic 1
 Light colour/type RGBW
 Required components:



Light distribution files





LED XM-L RGBW (XMLDCL HI)
 FWHM / FWTM 35.0° / 60.0°
 Efficiency 79 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type RGBW
 Required components:



Light distribution files



LED XQ-E HD
 FWHM / FWTM 34.0° / 59.0°
 Efficiency 77 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 4
 Light colour/type RGBW
 Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON CZ
FWHM / FWTM 31.0° / 62.0°
Efficiency 74 %
Peak intensity 1.9 cd/lm
LEDs/each optic 4
Light colour/type RGBW
Required components:



Light distribution files





LED SBM-40-RGBW
FWHM / FWTM 32.0° / 54.0°
Efficiency 79 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED NCSxE17A
FWHM / FWTM 30.0° / 54.0°
Efficiency 79 %
Peak intensity 2.4 cd/lm
LEDs/each optic 4
Light colour/type RGBW
Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):





LED NVSW219F
FWHM / FWTM 34.0° / 59.0°
Efficiency 80 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files





LED OSLO Pure 1414
FWHM / FWTM 32.0° / 55.0°
Efficiency 77 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour/type RGBW
Required components:



Light distribution files



LED Ostar-SMT RGB
FWHM / FWTM 34.0° / 51.0°
Efficiency 87 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):





LED SPF05F0A
FWHM / FWTM 34.0° / 57.0°
Efficiency 79 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type RGBW
Required components:



Light distribution files





LED SPF05F0B
FWHM / FWTM 35.0° / 58.0°
Efficiency 79 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type RGBW
Required components:



Light distribution files



LED SPF05F0C
FWHM / FWTM 32.0° / 57.0°
Efficiency 78 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type RGBW
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED OSTAR Stage (S2WN)
FWHM / FWTM 38.0° / 61.0°
Efficiency 92 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors

LED OSTAR Stage (S2WP)
FWHM / FWTM 36.0° / 54.4°
Efficiency 0 %
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)