

IRIS


Ø38 mm narrow beam (4-6°) TIR-lenses for narrow flood-, accent and searchlights and up to 7070 size LED packages

Highly efficient spot beam optic family supporting a wide range of LED sizes from 3535 to 7070 resulting in beam angles from 4° to 17°. Ideal for applications where high cd/m peak and narrow beam are required such as narrow floodlights, accent lights and searchlights.



PRODUCTS:

IRIS-IR




Dimensions: 38.0 mm x 38.0 mm

Height: 28.60 mm

~10° infrared spot beam with holder

IRIS




Dimensions: 38.0 mm x 38.0 mm

Height: 28.50 mm

~10° spot beam with holder

FCA12077_IRIS




Dimensions: 38.0 mm x 38.0 mm

Height: 27.10 mm

~5° real spot beam optimized for CREE XP-E. Assembly with holder and installation tape.

PRODUCTS:


IRIS-O



Dimensions: 38.0 mm x 38.0 mm
Height: 28.80 mm

~40° x 30° oval beam with sublens
and holder optimized for CREE
XM-L.


IRIS-M



Dimensions: 38.0 mm x 38.0 mm
Height: 30.00 mm

~25° medium beam with sublens
and holder


IRIS-SCREW



Dimensions: 38.0 mm x 38.0 mm
Height: 27.30 mm

~5° spot beam with holder optimized
for CREE XM-L. Assembly with
screws.


FCA12777_IRIS-M



Dimensions: 38.0 mm x 38.0 mm
Height: 29.20 mm

~25° medium beam optimized for
CREE XM-L. Assembly with holder,
sublens and installation tape.


IRIS



Dimensions: 38.0 mm x 38.0 mm
Height: 28.10 mm

~10° spot beam with holder
optimized for Luminus SST-50

FCA12104_IRIS




Dimensions: 38.0 mm x 38.0 mm
Height: 27.70 mm

~5° real spot beam optimized for
CREE XM-L. Assembly with holder
and installation tape.

PRODUCTS:


FCA12792_IRIS-M



Dimensions: 38.0 mm x 38.0 mm
Height: 28.60 mm

~25° medium beam optimized for CREE XP-E. Assembly with holder, sublens and installation tape.


IRIS-M



Dimensions: 38.0 mm x 38.0 mm
Height: 29.60 mm

~25° medium beam with sublens and holder optimized for Luminus SST-50


IRIS-IR-M



Dimensions: 38.0 mm x 38.0 mm
Height: 30.20 mm

~25° infrared medium beam with sublens and holder

IRIS-SCREW



Dimensions: 38.0 mm x 38.0 mm
Height: 26.90 mm

~5° real spot beam with holder optimized for CREE XP-E. Assembly with screws.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)