

# PRODUCT DATASHEET CA12570\_LAURA-W

## LAURA-W

~40° wide beam optimized for Nichia 19. Assembly with black holder and installation tape.

### **SPECIFICATION:**

Dimensions	21.6 x 21.6 mm
Height	12.9 mm
Fastening	tape
ROHS compliant	yes 🛈



### **MATERIALS:**


Component	Туре	Material	Colour	Finish
LAURA-W	Single lens	PMMA	clear	
LAURA-HLD-N19-BLK	Holder	PC	black	
ROSE-TAPE	Таре	Acrylic foam	black	

### **ORDERING INFORMATION:**

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12570_LAURA-W	Single lens	1440	360	180	7.9
» Box size: 451 x 254 x 152 mm					



## PRODUCT DATASHEET CA12570\_LAURA-W



See also our general installation guide: www.ledil.com/installation\_guide



### **OPTICAL RESULTS (MEASURED):**

### **Μ**ΝΙCΗΙΛ

LED	NCSxx19A	
FWHM / FWTM	40.0° / 60.0°	
Efficiency	83 %	
LEDs/each optic	1	
Light colour	White	
Required components:		

### **Μ**ΝΙCΗΙΛ

LED	NVSxx19A	
FWHM / FWTM	43.0° / 63.0°	
Efficiency	87 %	
LEDs/each optic	1	
Light colour	White	
Required components:		



### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

### LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B **Casic Motor Building** Shenzhen 518057 P.R.CHINA

### Local sales and technical support www.ledil.com/ where\_to\_buy

**Shipping locations** Salo, Finland Hong Kong, China

### **Distribution Partners** www.ledil.com/ where\_to\_buy