


## G2-LAURA-D-P

~13° diffused spot beam. Assembly with thinner white holder, installation tape and location pins.

### SPECIFICATION:

Dimensions	21.6 x 21.6
Height	13.1 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




### MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
LAURA-D	Single lens	PMMA	clear		
LAURA-LT-PIN-XP-HLD-WHT	Holder	PC	white		
ROSE-TAPE	Tape	Acrylic foam	black		

### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA13629_G2-LAURA-D-P » Box size: 451 x 254 x 152 mm	1440	360	180	5.9





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### OPTICAL RESULTS (MEASURED):



**LED** XB-H  
**FWHM / FWTM** 19.0° / 41.0°  
**Efficiency** 83 %  
**Peak intensity** 4.8 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files





**LED** XP-E  
**FWHM / FWTM** 13.0° / 31.0°  
**Efficiency** 93 %  
**Peak intensity** 9.3 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**

Light distribution files



**LED** XP-E2  
**FWHM / FWTM** 16.0° / 37.0°  
**Efficiency** 83 %  
**Peak intensity** 6.1 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**





Light distribution files

#### OPTICAL RESULTS (MEASURED):





LED XP-G2  
 FWHM / FWTM 19.0° / 40.0°  
 Efficiency 83 %  
 Peak intensity 5.1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files





LED XP-L HD  
 FWHM / FWTM 21.0° / 45.0°  
 Efficiency 81 %  
 Peak intensity 3.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED XP-L2  
 FWHM / FWTM 22.0° / 48.0°  
 Efficiency 84 %  
 Peak intensity 3.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:





Light distribution files

#### OPTICAL RESULTS (MEASURED):




LED XT-E  
FWHM / FWTM 19.0° / 41.0°  
Efficiency 82 %  
Peak intensity 4.7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files





LED LUXEON 3030 2D (Round LES)  
FWHM / FWTM 18.0° / 38.0°  
Efficiency 87 %  
Peak intensity 5.4 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED LUXEON TX  
FWHM / FWTM 18.0° / 40.0°  
Efficiency 86 %  
Peak intensity 5.2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (MEASURED):




**LED** NCSxx19A  
**FWHM / FWTM** 19.0° / 41.0°  
**Efficiency** 87 %  
**Peak intensity** 5 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files





**LED** NCSxx19B  
**FWHM / FWTM** 17.0° / 38.0°  
**Efficiency** 83 %  
**Peak intensity** 5.4 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**



Light distribution files



**LED** NVSW219D  
**FWHM / FWTM** 18.0° / 40.0°  
**Efficiency** 94 %  
**Peak intensity** 5 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**





Light distribution files

#### OPTICAL RESULTS (MEASURED):




LED NVSxx19A  
FWHM / FWTM 20.0° / 43.0°  
Efficiency 81 %  
Peak intensity 4.2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files





LED NVSxx19B/NVSxx19C  
FWHM / FWTM 19.0° / 42.0°  
Efficiency 83 %  
Peak intensity 4.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED OSLOM Square EC  
FWHM / FWTM 19.0° / 40.0°  
Efficiency 82 %  
Peak intensity 4.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (MEASURED):

### SAMSUNG

LED LH351D  
 FWHM / FWTM 21.0° / 46.0°  
 Efficiency 93 %  
 Peak intensity 3.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:





Light distribution files



SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2  
 FWHM / FWTM 18.0° / 39.0°  
 Efficiency 83 %  
 Peak intensity 4.9 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:





Light distribution files



SEOUL SEMICONDUCTOR

LED Z5M3  
 FWHM / FWTM 19.0° / 42.0°  
 Efficiency 93 %  
 Peak intensity 4.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files



#### OPTICAL RESULTS (SIMULATED):




LED XHP35 HI  
 FWHM / FWTM 14.0° / 26.0°  
 Efficiency 94 %  
 Peak intensity 12.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED XP-G3  
 FWHM / FWTM 14.0° / 28.0°  
 Efficiency 93 %  
 Peak intensity 11.6 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files






LED XQ-E HD  
 FWHM / FWTM 10.8° / 21.2°  
 Efficiency 94 %  
 Peak intensity 20.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files


#### OPTICAL RESULTS (SIMULATED):



#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED OSLON Signal  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 95 %  
 Peak intensity 24.2 cd/lm  
 LEDs/each optic 1  
 Light colour/type Red  
 Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors



LED OSLON Square CSSRM2/CSSRM3  
 FWHM / FWTM 12.0° / 25.0°  
 Efficiency 96 %  
 Peak intensity 14.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED OSLON Square Flat  
 FWHM / FWTM 9.0° / 19.0°  
 Efficiency 94 %  
 Peak intensity 26.1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED OSLON SSL 80  
FWHM / FWTM 10.0° / 22.0°  
Efficiency 95 %  
Peak intensity 18.7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**SAMSUNG**


LED LH351C  
FWHM / FWTM 14.0° / 26.0°  
Efficiency 94 %  
Peak intensity 12.4 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**SEMI**  
SEOUL SEMICONDUCTOR

LED Z8Y22P  
FWHM / FWTM 13.0° / 25.0°  
Efficiency 97 %  
Peak intensity 13.6 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)