

### LISA

Miniature TIR-lenses for jewellery shops, reading lights, torches and head lamps.

LISA series of lenses, measuring less than 10 mm in diameter and less than 7 mm tall, achieves up to 90 % light transmission efficiency through superior design and materials. Each lens is mounted in a molded polycarbonate (PC) housing and attaches to the PCB by means of locating pins or optional mounting clips and is built to maintain its physical integrity over the usable life of the luminaire.


### LISA

Ø10.8 mm variant with glue mounting for up to 3535 size LED packages



### PRODUCTS:

#### CP10641\_LISA-SS



**Dimensions: 10.8 mm x 10.8 mm**  
**Height: 7.30 mm**

~20° smooth spot beam optimized for  
CREE XP-E


#### CP10544\_LISA-SS



**Dimensions: 10.8 mm x 10.8 mm**  
**Height: 7.10 mm**

~20° smooth spot beam optimized for  
LUXEON Rebel

#### CP11627\_LISA-RS




**Dimensions: 10.8 mm x 10.8 mm**  
**Height: 7.30 mm**

~15° spot beam optimized for CREE  
XP-E

## PRODUCTS:

### CP10444\_LISA-SS




**Dimensions: 10.8 mm x 10.8 mm**

**Height: 7.30 mm**

~20° smooth spot beam optimized for  
Golden Dragon

### CP11626\_LISA-RS



**Dimensions: 11.0 mm x 11.0 mm**

**Height: 7.90 mm**

~15° spot beam optimized for Golden  
Dragon

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)