

MIRELLA-50-M-PIN

~30° medium beam

SPECIFICATION:

Dimensions	Ø 49.9
Height	23.9 mm
Fastening	pin
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish	Coating
MIRELLA-50-M-PIN	Reflector	PC	metal		lacquer



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C12481_MIRELLA-50-M-PIN » Box size: 480 x 280 x 300 mm	336	112	28	3.1





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):




LED SM4
FWHM / FWTM 35.0° / 73.0°
Efficiency 78 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL



Light distribution files




LED SM4
FWHM / FWTM 29.0° / 68.0°
Efficiency 80 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C13333_MIRELLA-CL



Light distribution files



LED MHB-A/B
FWHM / FWTM 28.0° / 80.0°
Efficiency 88 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):




LED MHB-A/B
FWHM / FWTM 35.0° / 76.0°
Efficiency 83 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C12479_MIRELLA-DL



Light distribution files





LED MHB-A/B
FWHM / FWTM 34.0° / 78.0°
Efficiency 83 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C13333_MIRELLA-CL



Light distribution files



LED XHP50
FWHM / FWTM 32.0° / 74.0°
Efficiency 86 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C12479_MIRELLA-DL




Light distribution files

OPTICAL RESULTS (MEASURED):




LED XHP50
 FWHM / FWTM 37.0° / 78.0°
 Efficiency 83 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C13723_MIRELLA-RZL



Light distribution files





LED XHP50
 FWHM / FWTM 32.0° / 76.0°
 Efficiency 85 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C13333_MIRELLA-CL



Light distribution files



LED XHP50
 FWHM / FWTM 25.0° / 77.0°
 Efficiency 90 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):





LED XM-L
FWHM / FWTM 28.0° / 72.0°
Efficiency 84 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C13333_MIRELLA-CL



Light distribution files





LED XM-L
FWHM / FWTM 35.0° / 76.0°
Efficiency 80 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL



Light distribution files



LED XM-L
FWHM / FWTM 24.0° / 56.0°
Efficiency 89 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):





LED XM-L RGBW (XMLCTW)
FWHM / FWTM 37.0° / 76.0°
Efficiency 83 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C13723_MIRELLA-RZL



Light distribution files




LED XM-L2
FWHM / FWTM 33.0° / 74.0°
Efficiency 82 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL



Light distribution files



LED XM-L2
FWHM / FWTM 22.0° / 58.0°
Efficiency 91 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):





LED XP-G
FWHM / FWTM 34.0° / 74.0°
Efficiency 81 %
Peak intensity 1.6 cd/m
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL



Light distribution files




LED XP-G
FWHM / FWTM 24.0° / 68.0°
Efficiency 83 %
Peak intensity 2.7 cd/m
LEDs/each optic 1
Light colour/type White
Required components:
 C13333_MIRELLA-CL



Light distribution files



LED XP-G
FWHM / FWTM 24.0° / 53.0°
Efficiency 86 %
Peak intensity 3.3 cd/m
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OPTICAL RESULTS (MEASURED):




LED XP-G2
FWHM / FWTM 22.0° / 76.0°
Efficiency 88 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files





LED XP-G2
FWHM / FWTM 30.0° / 74.0°
Efficiency 83 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C12479_MIRELLA-DL



Light distribution files



LED XP-L HI
FWHM / FWTM 17.0° / 48.0°
Efficiency 88 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):




LED XT-E
FWHM / FWTM 22.0° / 64.0°
Efficiency 81 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C13333_MIRELLA-CL



Light distribution files





LED XT-E
FWHM / FWTM 23.0° / 51.0°
Efficiency 85 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XT-E
FWHM / FWTM 32.0° / 73.0°
Efficiency 78 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL





Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON 5050 Round LES
 FWHM / FWTM 22.0° / 59.0°
 Efficiency 90 %
 Peak intensity 3.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files





LED LUXEON A
 FWHM / FWTM 24.0° / 69.0°
 Efficiency 84 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C13333_MIRELLA-CL



Light distribution files



LED LUXEON A
 FWHM / FWTM 22.0° / 52.0°
 Efficiency 87 %
 Peak intensity 3.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON A
FWHM / FWTM 34.0° / 75.0°
Efficiency 80 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C12479_MIRELLA-DL



Light distribution files





LED LUXEON C
FWHM / FWTM 39.0° / 79.0°
Efficiency 74 %
Peak intensity 1.2 cd/lm
LEDs/each optic 4
Light colour/type RGBW
Required components:
C13723_MIRELLA-RZL



Light distribution files



LED LUXEON M/MX
FWHM / FWTM 33.0° / 74.0°
Efficiency 84 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C13333_MIRELLA-CL




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON M/MX
 FWHM / FWTM 38.0° / 78.0°
 Efficiency 81 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C12479_MIRELLA-DL



Light distribution files





LED LUXEON M/MX
 FWHM / FWTM 24.0° / 63.0°
 Efficiency 87 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON MZ
 FWHM / FWTM 20.0° / 47.0°
 Efficiency 88 %
 Peak intensity 4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON MZ
FWHM / FWTM 27.0° / 69.0°
Efficiency 84 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL



Light distribution files





LED LUXEON Z
FWHM / FWTM 31.0° / 71.0°
Efficiency 83 %
Peak intensity 1.7 cd/lm
LEDs/each optic 4
Light colour/type RGBW
Required components:
 C13723_MIRELLA-RZL



Light distribution files



LED NS9x383
FWHM / FWTM 32.0° / 74.0°
Efficiency 83 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C12479_MIRELLA-DL




Light distribution files

OPTICAL RESULTS (MEASURED):




LED NS9x383
 FWHM / FWTM 24.0° / 78.0°
 Efficiency 88 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files





LED NV4x144A
 FWHM / FWTM 27.0° / 73.0°
 Efficiency 89 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED Duris S8
 FWHM / FWTM 26.0° / 70.0°
 Efficiency 84 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C13333_MIRELLA-CL




Light distribution files

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors



LED Duris S8
 FWHM / FWTM 22.0° / 58.0°
 Efficiency 88 %
 Peak intensity 3.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files

OSRAM
Opto Semiconductors



LED Duris S8
 FWHM / FWTM 28.0° / 69.0°
 Efficiency 84 %
 Peak intensity 2.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C12479_MIRELLA-DL



Light distribution files

OSRAM
Opto Semiconductors

LED OSLOM Square EC
 FWHM / FWTM 22.0° / 49.0°
 Efficiency 84 %
 Peak intensity 3.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors



LED OSLON Square EC
 FWHM / FWTM 32.0° / 75.0°
 Efficiency 79 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C12479_MIRELLA-DL



Light distribution files

OSRAM
Opto Semiconductors



LED OSLON Square EC
 FWHM / FWTM 22.0° / 67.0°
 Efficiency 83 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C13333_MIRELLA-CL



Light distribution files

OSRAM
Opto Semiconductors

LED Ostar-SMT RGB
 FWHM / FWTM 34.0° / 74.0°
 Efficiency 83 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C13723_MIRELLA-RZL





Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG


LED LH508A
FWHM / FWTM 24.0° / 78.0°
Efficiency 88 %
Peak intensity 2.4 cd/m
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED F50360 (RGB)
FWHM / FWTM 33.0° / 76.0°
Efficiency 82 %
Peak intensity 1.8 cd/m
LEDs/each optic 1
Light colour/type White
Required components:
C13723_MIRELLA-RZL




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED J Series 7070B K Class
FWHM / FWTM 28.0° / 68.0°
Efficiency 92 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XHP35 HD
FWHM / FWTM 28.0° / 77.0°
Efficiency 92 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED LUXEON 5258
FWHM / FWTM 23.0° / 45.0°
Efficiency 91 %
Peak intensity 3.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):





LED LUXEON 7070
 FWHM / FWTM 28.0° / 66.0°
 Efficiency 91 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files





LED OSCONIQ P 7070
 FWHM / FWTM 31.0° / 72.0°
 Efficiency 88 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C12479_MIRELLA-DL



Light distribution files



LED OSCONIQ P 7070
 FWHM / FWTM 26.0° / 63.0°
 Efficiency 91 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:





Light distribution files

OPTICAL RESULTS (SIMULATED):




LED OSCONIQ P 7070
FWHM / FWTM 29.0° / 70.0°
Efficiency 87 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C13333_MIRELLA-CL



Light distribution files




LED LH351D
FWHM / FWTM 26.0° / 54.0°
Efficiency 90 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED Z8Y22P
FWHM / FWTM 19.0° / 44.0°
Efficiency 89 %
Peak intensity 4.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)