

## TINA2-W

~45° wide beam optimized for Nichia NCSxx19.  
Assembly with holder, installation tape and location pins.

### SPECIFICATION:

|                |           |
|----------------|-----------|
| Dimensions     | Ø 16.1    |
| Height         | 9.3 mm    |
| Fastening      | tape, pin |
| ROHS compliant | yes ⓘ     |




LEDiL®

### MATERIALS:

| Component           | Type        | Material     | Colour | Finish | Length |
|---------------------|-------------|--------------|--------|--------|--------|
| TINA2-W-XP          | Single lens | PMMA         | clear  |        | 16.1   |
| TINA2-HLD-NCS19-BLK | Holder      | PC           | black  |        | 16.1   |
| TINA-TAPE3          | Tape        | Acrylic foam | black  |        | 16.0   |

### ORDERING INFORMATION:



| Component                      |             | Qty in box | MOQ | MPQ | Box weight (kg) |
|--------------------------------|-------------|------------|-----|-----|-----------------|
| CA11022_TINA2-W                | Single lens | 4140       |     | 230 | 8.3             |
| » Box size: 451 x 241 x 298 mm |             |            |     |     |                 |



### OPTICAL RESULTS (MEASURED):





LED NCSxx19A  
FWHM / FWTM 46.0° / 78.0°  
Efficiency 88 %  
Peak intensity 1.3 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files





LED NVSxx19A  
FWHM / FWTM 58.0° / 88.0°  
Efficiency 82 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

### SAMSUNG

LED LH181A  
FWHM / FWTM 36.0° / 58.0°  
Efficiency 84 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:





Light distribution files

## OPTICAL RESULTS (MEASURED):

### SAMSUNG

|                      |               |
|----------------------|---------------|
| LED                  | LH181B        |
| FWHM / FWTM          | 38.0° / 59.0° |
| Efficiency           | 89 %          |
| Peak intensity       | 2 cd/lm       |
| LEDs/each optic      | 1             |
| Light colour/type    | White         |
| Required components: |               |




Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED NCSxE17A  
FWHM / FWTM 45.0° / 70.0°  
Efficiency 86 %  
Peak intensity 1.3 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:



Light distribution files




LED NVSxE21A  
FWHM / FWTM 45.5° / 63.0°  
Efficiency 92 %  
Peak intensity 1.8 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED NVSxE21A  
FWHM / FWTM 40.0° / 60.0°  
Efficiency 90 %  
Peak intensity 2.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)