

- Notes**
- PCB level
 - Heat sink level
 - Led location
- For more details about compatible LEDs please check measured results on www.ledil.com and 3D model for more detailed mechanical information
See installation details page 2.

COMPONENTS				
INDEX	PRODUCT	TYPE	MATERIAL	COLOUR/COATING
1	C16400_STRADA-IP-2X6-PX	LENS	PMMA	CLEAR
2	C14018_2X6-SEAL25	SEAL	SILICONE	WHITE

MECHANICAL DRAWING			LEDiL [®]		
PRODUCT CS16401_STRADA-IP-2X6-PX					This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.
Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: Up to 30mm class M, otherwise class C. According to DIN ISO 2768-2 Form and position: class L	FIRST ANGLE PROJECTION: 				
SCALE	1:1	SIZE	A3	SHEET	1/2

4

3

2

1

4

3

2

1

Recommended
PCB max. size 45x146mm

Location pin cutout

PCB geometry
for reference only

LED geometry
for reference only

SEAL

LENS geometry
for reference only

M3 screw recommended
for fixing

Use washer with screw if possible

Recommended max. torque
for screw fixing: 0.6Nm

Notes

For more details about installation please see
LEDiL Installation Guide on www.ledil.com


MECHANICAL DRAWING

PRODUCT

CS16401_STRADA-IP-2X6-PX

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

FIRST ANGLE PROJECTION:



LEDiL[®]

This drawing is the property
of LEDiL Oy. It may not be
reproduced, copied or
communicated without a written
agreement with LEDiL Oy.

SCALE

-

SIZE

A3

SHEET

2/2