

AMBER-8-HB-M


~60° medium beam for industrial applications

SPECIFICATION:

Dimensions	49.5 x 49.5
Height	7.1 mm
Fastening	pin, screw
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
AMBER-8-HB-M	Multi-lens	PMMA	amber		



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C19208_AMBER-8-HB-M » Box size: 480 x 280 x 300 mm	800	160	160	4.4





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED	XP-G3
FWHM / FWTM	76.0° / 137.0°
Efficiency	86 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Amount of Blue light (380-500 nm)	1.2 %
CCT (LED/with lens)*	3726K/2673K
Required components:	



*the measured CCT with lens doesn't follow the Black Body Locus line





LED	LUXEON HL2X-D
FWHM / FWTM	73.0° / 122.0°
Efficiency	86 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Amount of Blue light (380-500 nm)	1.7 %
CCT (LED/with lens)*	3828K/2695K
Required components:	



Light distribution files



LED	NVSW219F
FWHM / FWTM	76.0° / 131.0°
Efficiency	86 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Amount of Blue light (380-500 nm)	1.2 %
CCT (LED/with lens)*	3749K/2657K
Required components:	





Light distribution files

OPTICAL RESULTS (MEASURED):





LED OSLON Square CSSRM2/CSSRM3
 FWHM / FWTM 70.0° / 124.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 1.3 %
 CCT (LED/with lens)* 3848K/2683K
 Required components:



Light distribution files





LED LH351C
 FWHM / FWTM 73.0° / 126.0°
 Efficiency 87 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 1.4 %
 CCT (LED/with lens)* 3752K/2710K
 Required components:



Light distribution files



LED Z5M4
 FWHM / FWTM 73.0° / 119.0°
 Efficiency 87 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 1.4 %
 CCT (LED/with lens)* 3557K/2589K
 Required components:



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)