

ALISE-110-M


~24° medium beam

SPECIFICATION:

Dimensions	Ø 110.0
Height	65 mm
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish	Coating
ALISE-110-M	Reflector	Aluminium	metal		Anodized



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C16900_ALISE-110-M » Box size: 500 x 375 x 250 mm	300	100	25	11.2




See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):



LED CMU22xx
FWHM / FWTM 25.0° / 58.0°
Efficiency 87 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
Bender Wirth: 431 Typ L3




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED: Vero SE 18
FWHM / FWTM: 20.0° / 49.0°
Efficiency: 92 %
Peak intensity: 4.7 cd/lm
LEDs/each optic: 1
Light colour/type: White
Required components:



Light distribution files

CITIZEN


LED: CLL04x/CLU04x
FWHM / FWTM: 24.0° / 55.0°
Efficiency: 91 %
Peak intensity: 3.4 cd/lm
LEDs/each optic: 1
Light colour/type: White
Required components:



Light distribution files



LED: CMA1840
FWHM / FWTM: 18.0° / 41.0°
Efficiency: 88 %
Peak intensity: 5.3 cd/lm
LEDs/each optic: 1
Light colour/type: White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED CMT28xx
 FWHM / FWTM 25.0° / 56.0°
 Efficiency 92 %
 Peak intensity 3.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED CXA/B 15xx
 FWHM / FWTM 14.0° / 34.0°
 Efficiency 88 %
 Peak intensity 7.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED CXA/B 1830
 FWHM / FWTM 18.0° / 42.0°
 Efficiency 88 %
 Peak intensity 5.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED CXA/B 30xx
FWHM / FWTM 21.0° / 51.0°
Efficiency 92 %
Peak intensity 4.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED LUXEON CoB 1208
FWHM / FWTM 18.0° / 42.0°
Efficiency 88 %
Peak intensity 5.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED CxM-22 (28x28)
FWHM / FWTM 24.0° / 56.0°
Efficiency 88 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED COB J-Type
FWHM / FWTM 18.0° / 40.0°
Efficiency 88 %
Peak intensity 5.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED LC003D / LC006D / LC009D / LC013D
FWHM / FWTM 14.0° / 34.0°
Efficiency 88 %
Peak intensity 7.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED LC016D / LC019D / LC026D / LC033D
FWHM / FWTM 18.0° / 44.0°
Efficiency 87 %
Peak intensity 5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LC040D / LC060D / LC080D
FWHM / FWTM	24.0° / 55.0°
Efficiency	91 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)