

AMY-50-O

~20 + 50° oval beam

SPECIFICATION:

Dimensions	Ø 49.9
Height	11 mm
Fastening	socket
ROHS compliant	yes 🛈



MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
AMY-50-O	Single lens	PMMA	clear		
AMY-50-HLD2-C-ASYM	Holder C	PC	black		
AMY-50-HLD2-B-ASYM	Holder B	PC	black		
AMY-50-HLD2-C-WHT-ASYM	Holder C	PC	white		
AMY-50-HLD2-B-WHT-ASYM	Holder B	PC	white		






ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C18490_AMY-50-O	690	120	30	9.7
Assembly				
CP19158_AMY-50-O-B2-WHT	510	120	30	8.9
CP19147_AMY-50-O-C2-WHT	510	120	30	8.5
CP19138_AMY-50-O-B2	510	120	30	8.9
CP19129_AMY-50-O-C2	510	120	30	8.5

PRODUCT DATASHEET AMY-50-O



See also our general installation guide: www.ledil.com/installation_guide

3/21



OPTICAL RESULTS (MEASURED):


CITIZEN

 LED
 CLU02x (LES10)

 Ordering code
 CP19129_AMY-50-O-C2

 FWHM / FWTM
 51.0 + 21.0° / 83.0 + 48.0°

Efficiency 88 %
LEDs/each optic 1
Light colour/type White
Required components:
F17435_HEKLA-G2-C



Light distribution files


CITIZEN

LED CLU02x (LES10)

Ordering code CP19138_AMY-50-O-B2

FWHM / FWTM 51.0 + 21.0° / 83.0 + 48.0°

Efficiency 88 %
LEDs/each optic 1
Light colour/type White
Required components:
BJB: 47.360.1020




Light distribution files

CITIZEN

LED CLU02x (LES10)

Ordering code CP19147_AMY-50-O-C2-WHT FWHM / FWTM 52.0 + 20.0° / 84.0 + 47.0°

Efficiency 95 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17435_HEKLA-G2-C




Light distribution files

OPTICAL RESULTS (MEASURED):



LED CTM-14 (Tunable White) Gen2
Ordering code CP19129_AMY-50-O-C2
FWHM / FWTM 47.0 + 26.0° / 87.0 + 56.0°

Efficiency 85 %
LEDs/each optic 1
Light colour/type White
Required components:
C16142_HEKLA-SOCKET-K
Bender Wirth: 442 Typ L8



Light distribution files

PHILIPS

LED Fortimo SLM C TW L06A 1313 G7N


Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 53.0 + 16.0° / 79.0 + 38.0°

Efficiency 89 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K Bender Wirth: 508 Typ L8



Light distribution files

PHILIPS


LED Fortimo SLM C TW L09A 1919 G7N

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 51.0 + 20.0° / 83.0 + 45.0°

Efficiency 88 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components: C16142_HEKLA-SOCKET-K Bender Wirth: 501 Typ L8



Light distribution files

bridgelux


LED V10 Gen 8-9

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 57.0 + 20.0° / 85.0 + 45.0°

Efficiency 88 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

BJB: 47.360.1020



Light distribution files

bridgelux.


LED V3 HD Gen 8

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 58.0 + 14.0° / 82.0 + 40.0°

Efficiency 92 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

F15253_HEKLA-SOCKET-A



Light distribution files

bridgelux


LED V4 HD Gen 8

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 58.0 + 16.0° / 82.0 + 40.0°

Efficiency 92 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

F15253_HEKLA-SOCKET-A



bridgelux

LED V6 HD Gen 8

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 58.0 + 16.0° / 83.0 + 41.0°

Efficiency 91 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

F15255_HEKLA-SOCKET-C

Light distribution files

bridgelux.


LED VERO13

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 51.0 + 24.0° / 86.0 + 54.0°

Efficiency 88 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

C16142_HEKLA-SOCKET-K



Light distribution files

bridgelux.

 LED
 Vesta SE 13mm TW

 Ordering code
 CP19129_AMY-50-O-C2


 FWHM / FWTM
 52.0 + 26.0° / 88.0 + 50.0°

Efficiency 81 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K




CITIZEN

LED CLU02x (LES10)

Ordering code CP19147_AMY-50-O-C2-WHT FWHM / FWTM 58.0 + 20.0° / 86.0 + 44.0°

Efficiency 95 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components: F17435_HEKLA-G2-C




Light distribution files

CITIZEN

LED CLU02x (LES10)
Ordering code C18490_AMY-50-O
FWHM / FWTM 56.0 + 22.0° / 86.0 + 48.0°

Efficiency 91 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components: F17435_HEKLA-G2-C



Light distribution files

CITIZEN


LED CLU700/701/702/703

Ordering code CP19129_AMY-50-O-C2

FWHM / FWTM 58.0 + 16.0° / 82.0 + 40.0°

Efficiency 89 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White

Required components: F17435_HEKLA-G2-C



CITIZEN

LED CLU700/701/702/703

Ordering code CP19138_AMY-50-O-B2

FWHM / FWTM 58.0 + 12.0° / 78.0 + 38.0°

Efficiency 90 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

BJB: 47.360.1020


Light distribution files

CITIZEN

LED CLU700/701/702/703
Ordering code C18490_AMY-50-O
FWHM / FWTM 60.0 + 18.0° / 86.0 + 43.0°

Efficiency 92 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White

Required components: F17435_HEKLA-G2-C



Light distribution files


CITIZEN

LED CLU7B2

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 58.0 + 14.0° / 79.0 + 38.0°

Efficiency 90 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

F17435_HEKLA-G2-C



CITIZEN


LED CLU7B2

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 58.0 + 14.0° / 78.0 + 38.0°

Efficiency 90 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

BJB: 47.360.1020 Light distribution files




CITIZEN

LED CLU7B2

Ordering code C18490_AMY-50-O FWHM / FWTM 60.0 + 16.0° / 84.0 + 44.0°

Efficiency 93 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour/type White

Required components: F17435_HEKLA-G2-C



Light distribution files




LED CMU10xx

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 58.0 + 20.0° / 84.0 + 46.0°

Efficiency 88 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

BJB: 47.360.1020





LED LUXEON CX Plus CoB L08 (Gen2)

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 47.0 + 26.0° / 86.0 + 54.0°

Efficiency 87 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Light distribution files

Bender Wirth: 637a Hekla

UMILEDS

LED LUXEON CX Plus CoB - HD S01H4

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 58.0 + 14.0° / 82.0 + 36.0°

Efficiency 91 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Light distribution files

Bender Wirth: 634c Bayonet35L

MILEDS

LED LUXEON CX Plus CoB - HD S02H6

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 58.0 + 16.0° / 83.0 + 40.0°

Efficiency 91 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files

Bender Wirth: 634c Bayonet35L




LED LUXEON CX Plus CoB - HD S04H9

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 54.0 + 20.0° / 84.0 + 44.0°

Efficiency 89 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:



Light distribution files




LED LUXEON CX Plus CoB L04 / L05 (Gen2)

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 52.0 + 23.0° / 86.0 + 50.0°

Efficiency 87 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

F15254_HEKLA-SOCKET-B



Light distribution files




LED LUXEON CX Plus CoB M02 / M03 (Gen2)

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 54.0 + 18.0° / 84.0 + 44.0°

Efficiency 89 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

F15256_HEKLA-SOCKET-D



Light distribution files



 LED
 CHM-11 XH (19x19)

 Ordering code
 CP19129_AMY-50-O-C2

 FWHM / FWTM
 56.0 + 18.0° / 84.0 + 44.0°

Efficiency 89 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components: F15859_HEKLA-SOCKET-I

Light distribution files



 LED
 CTM-14 (Tunable White) Gen2

 Ordering code
 CP19129_AMY-50-O-C2


 FWHM / FWTM
 48.0 + 24.0° / 86.0 + 52.0°

Efficiency 86 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K



Light distribution files

Bender Wirth: 442 Typ L8



 LED
 CTM-6 (Tunable White) Gen2

 Ordering code
 CP19129_AMY-50-O-C2

 FWHM / FWTM
 57.0 + 16.0° / 82.0 + 41.0°

Efficiency 90 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Light distribution files

Bender Wirth: 495 Typ L8

Published: 08/11/2023



 LED
 CTM-9 (Tunable White) Gen2

 Ordering code
 CP19129_AMY-50-O-C2


 FWHM / FWTM
 54.0 + 18.0° / 82.0 + 43.0°

Efficiency 88 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K



Light distribution files

Bender Wirth: 495 Typ L8



LED CxM-6 (13.5x13.5)
Ordering code CP19138_AMY-50-O-B2
FWHM / FWTM 56.0 + 15.0° / 82.0 + 38.0°

Efficiency 90 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

304*
304*
304*
304*
304*
304*
304*
304*

Light distribution files


BJB: 47.360.1020

WNICHIA

LED COB J-Type

Ordering code CP19126_AMY-50-WW-C2 FWHM / FWTM 50.0 + 28.0° / 88.0 + 56.0°

Efficiency 87 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



WNICHIA

 LED
 COB L-Type (LES 11)

 Ordering code
 CP19129_AMY-50-O-C2

 FWHM / FWTM
 54.0 + 22.0° / 86.0 + 49.0°

Efficiency 88 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

F15858_HEKLA-SOCKET-H

Light distribution files

WNICHIA

 LED
 COB L-Type (LES 9)


 Ordering code
 CP19129_AMY-50-O-C2

 FWHM / FWTM
 55.0 + 18.0° / 84.0 + 43.0°

Efficiency 90 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

F15858_HEKLA-SOCKET-H



Light distribution files

WNICHIA

LED COB S-Type (LES 6)
Ordering code CP19138_AMY-50-O-B2
FWHM / FWTM 58.0 + 16.0° / 82.0 + 40.0°

Efficiency 91 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Light distribution files

Bender Wirth: 652a Bayonet35L

WNICHIA

 LED
 COB S-Type (LES 7)


 Ordering code
 CP19138_AMY-50-O-B2

 FWHM / FWTM
 58.0 + 18.0° / 84.0 + 42.0°

Efficiency 90 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Bender Wirth: 652a Bayonet35L



Light distribution files

WNICHIA

 LED
 COB S-Type (LES 7)


 Ordering code
 CP19129_AMY-50-O-C2

 FWHM / FWTM
 59.0 + 18.0° / 82.0 + 41.0°

Efficiency 88 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Bender Wirth: 652a Hekla



Light distribution files

WNICHIA

_ED COB T-Type

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 58.0 + 16.0° / 84.0 + 40.0°

Efficiency 91 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Bender Wirth: 652a Bayonet35L

908* 908* 798* 908* 608* 608* 508* 158* 908*



LED NJCWL024Z-V1MT: COB L-Type Tunable White

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 57.0 + 16.0° / 82.0 + 40.0°

Efficiency 89 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Light distribution files

Bender Wirth: 497 Typ L8 HV

WNICHIA

LED NJNWS012Z-V1MT: COB S-Type Tunable White


Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 58.0 + 16.0° / 80.0 + 40.0°

Efficiency 90 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K



Light distribution files

Bender Wirth: 495 Typ L8 HV

WNICHIA

LED NVCWJ024Z-V1MT: COB J-Type Tunable White

Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 54.0 + 20.0° / 84.0 + 47.0°

Efficiency 88 %
Peak intensity 2 cd/lm
LEDs/each optic 1

Light colour/type Tunable White

Required components:

C16142_HEKLA-SOCKET-K

908* 908* 908* 908* 908* 908* 908*

Light distribution files

Bender Wirth: 498 Typ L8 HV

17/21

SAMSUNG

LED LC003D / LC006D / LC009D / LC013D

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM $55.0 + 20.0^{\circ} / 84.0 + 45.0^{\circ}$

Efficiency 89 % Peak intensity 2.1 cd/lm LEDs/each optic Light colour/type White

Required components:

Light distribution files

BJB: 47.360.1020

SAMSUNG

LFD LC010C G2

CP19138_AMY-50-O-B2 Ordering code FWHM / FWTM 58.0 + 16.0° / 81.0 + 38.0°

Efficiency 90 % Peak intensity 2.6 cd/lm LEDs/each optic White Light colour/type

Required components:

Light distribution files

BJB: 47.360.1020

SAMSUNG


LC010T (Tunable White) Ordering code CP19129_AMY-50-O-C2 FWHM / FWTM 56.0 + 18.0° / 82.0 + 42.0°

Efficiency 89 % 2.4 cd/lm Peak intensity LEDs/each optic

Tunable White Light colour/type

Required components:

C16142_HEKLA-SOCKET-K



Light distribution files

Bender Wirth: 501 Typ L8

Published: 08/11/2023

SAMSUNG

LED LC016D / LC019D / LC026D / LC033D

Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM $48.0 + 28.0^{\circ} / 87.0 + 57.0^{\circ}$

Efficiency 83 % Peak intensity 1.5 cd/lm LEDs/each optic Light colour/type White

Required components:

Light distribution files

BJB: 47.360.1010

SAMSUNG

LFD LC020C G2

CP19138_AMY-50-O-B2 Ordering code FWHM / FWTM 56.0 + 19.0° / 84.0 + 44.0°

Efficiency 88 % Peak intensity 2.2 cd/lm LEDs/each optic White Light colour/type

Required components:

Light distribution files

BJB: 47.360.1010

SAMSUNG

LC030C/040C G2 Ordering code CP19138_AMY-50-O-B2 FWHM / FWTM 52.0 + 23.0° / 84.0 + 50.0°

Efficiency 86 % 1.8 cd/lm Peak intensity LEDs/each optic White Light colour/type


Required components:

Light distribution files

BJB: 47.360.1010

19/21





Published: 08/11/2023



PRODUCT DATASHEET AMY-50-O

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 7 FI-24100 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Poznan, Poland Hong Kong, China

Distribution Partners

21/21

www.ledil.com/ where_to_buy