

## AMY-50-ZOOM

Infinitely adjustable beam from 20 to 50 degrees

## SPECIFICATION:

Dimensions	Ø 49.9
Height	13.6 mm
Fastening	socket
ROHS compliant	yes ⓘ


## MATERIALS:


Component	Type	Material	Colour	Finish	Length (mm)
AMY-50-ZOOM	Single lens	PMMA	clear	gloss	
AMY-50-ZOOM-SUB	Sublens	PMMA	clear	matt	
AMY-50-HLD2-C	Holder C	PC	black		
AMY-50-HLD2-B	Holder B	PC	black		
AMY-50-HLD2-C-WHT	Holder C	PC	white		
AMY-50-HLD2-B-WHT	Holder B	PC	white		



## ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C18646_AMY-50-ZOOM	420	120	30	7.6
C18647_AMY-50-ZOOM-SUB	420	120	30	4.4
<b>Assembly</b>				
CP19159_AMY-50-ZOOM-B2-WHT	420	120	30	9.0
CP19148_AMY-50-ZOOM-C2-WHT	420	120	30	8.7
CP19139_AMY-50-ZOOM-B2	420	120	30	9.0
CP19130_AMY-50-ZOOM-C2	420	120	30	8.7







See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)



### OPTICAL RESULTS (MEASURED):



LED CTM-14 (Tunable White) Gen2  
 Ordering code CP19130\_AMY-50-ZOOM-C2  
 FWHM / FWTM 28.0 + 52.0° / 62.0 + 87.0°  
 Efficiency 73 %  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
   C16142\_HEKLA-SOCKET-K  
   C18647\_AMY-50-ZOOM-SUB  
   Bender Wirth: 442 Typ L8




Light distribution files

### OPTICAL RESULTS (SIMULATED):




**LED** Vesta SE 13mm TW  
**Ordering code** CP19130\_AMY-50-ZOOM-C2  
**FWHM / FWTM** 26.0 + 48.0° / 50.0 + 83.0°  
**Efficiency** 77 %  
**Peak intensity** 2.5 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** Tunable White  
**Required components:**  
 C16142\_HEKLA-SOCKET-K  
 C18647\_AMY-50-ZOOM-SUB

Light distribution files



**LED** Duris S8  
**Ordering code** CP19130\_AMY-50-ZOOM-C2  
**FWHM / FWTM** 13.0 + 43.0° / 28.0 + 68.0°  
**Efficiency** 83 %  
**Peak intensity** 9.7 cd/lm  
**LEDs/each optic** 1  
**Light colour/type** White  
**Required components:**  
 C16142\_HEKLA-SOCKET-K  
 C18647\_AMY-50-ZOOM-SUB

Light distribution files



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)