

CLAUDIA-60

60° wide beam

SPECIFICATION:

Dimensions	279.4 x 29.3 mm
Height	9.6 mm
Fastening	clips
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish	Length
CLAUDIA-60	Linear lens	PMMA	clear		279.4

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C16664_CLAUDIA-60 » Box size: 400 x 300 x 300 mm	216	96	12	6.4






See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED J Series 2835
 FWHM / FWTM 54.0° / 76.0°
 Efficiency 93 %
 Peak intensity 1.1 cd/lm
 LEDs/each optic 2
 Light colour/type White
 Required components:



Light distribution files





LED LUXEON 3030 2D (Square LES)
 FWHM / FWTM 50.0° / 73.0°
 Efficiency 89 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 2
 Light colour/type White
 Required components:



Light distribution files



LED LinLED 280x26mm 1300lm 840 2C 42V Opt G1
 FWHM / FWTM 55.0° / 73.0°
 Efficiency 93 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):

NICHIA



LED	NF2x757G
FWHM / FWTM	55.0° / 76.0°
Efficiency	92 %
Peak intensity	1.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors

LED	Duris S5 (2 chip)
FWHM / FWTM	55.0° / 78.0°
Efficiency	92 %
Peak intensity	1.1 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED J Series 2835
FWHM / FWTM 45.0° / 67.0°
Efficiency 94 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED LUXEON 2835 Line
FWHM / FWTM 47.0° / 69.0°
Efficiency 94 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files






LED NF2x757G
FWHM / FWTM 47.0° / 68.0°
Efficiency 94 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files


OPTICAL RESULTS (SIMULATED):



OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LM28xB Series
FWHM / FWTM 68.0° / 86.0°
Efficiency 84 %
Peak intensity 0.6 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:



Light distribution files

SAMSUNG


LED LM28xB Series
FWHM / FWTM 44.0° / 66.0°
Efficiency 94 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files


SAMSUNG

LED LM28xB Series
FWHM / FWTM 54.0° / 73.0°
Efficiency 93 %
Peak intensity 1.3 cd/lm
LEDs/each optic 2
Light colour/type White
Required components:



Light distribution files

OPTICAL RESULTS (SIMULATED):

 SEOUL SEMICONDUCTOR		
LED	SEOUL DC 3528	
FWHM / FWTM	49.0° / 70.0°	
Efficiency	94 %	
Peak intensity	1.5 cd/lm	
LEDs/each optic	1	
Light colour/type	White	
Required components:		

Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)