

DAISY-2X2-W-D

~50° wide beam. Variant with diffused lenses.

SPECIFICATION:

Dimensions	79.5 x 79.5 mm
Height	21 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
C17257_DAISY-2X2-W-D	Multi-lens	PMMA	milky	
C17484_DAISY-2X2-SHD-WHT-MATT	Shade	PC	white	matt
C17483_DAISY-2X2-SHD-MATT	Shade	PC	black	matt
C16875_DAISY-2X2-SHD-WHT	Shade	PC	white	gloss
C16866_DAISY-2X2-SHD	Shade	PC	black	gloss


ORDERING INFORMATION:

Quantities for one set:

Multi-lens	1
Shade	1



Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17257_DAISY-2X2-W-D » Box size: 400 x 300 x 300 mm	Multi-lens	440	440	20	5.7
C17483_DAISY-2X2-SHD-MATT » Box size: 400 x 300 x 300 mm	Shade	186	440	20	5.2
C16866_DAISY-2X2-SHD » Box size: 400 x 300 x 300 mm	Shade	186	440	20	5.3
C17484_DAISY-2X2-SHD-WHT-MATT » Box size: 400 x 300 x 300 mm	Shade	186	440	20	5.4
C16875_DAISY-2X2-SHD-WHT » Box size: 400 x 300 x 300 mm	Shade	186	440	20	5.3





See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):





LED LIGHT ENGINE DAISY 16 LEDs 62mm x 62mm
FWHM / FWTM 64.5° / 92.0°
Efficiency 89 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C16875_DAISY-2X2-SHD-WHT





LED LIGHT ENGINE DAISY 16 LEDs 62mm x 62mm
FWHM / FWTM 63.5° / 91.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17536_DAISY-2X2-SHD-MET-MATT



LED LIGHT ENGINE DAISY 16 LEDs 62mm x 62mm
FWHM / FWTM 63.0° / 88.0°
Efficiency 77 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17483_DAISY-2X2-SHD-MATT





LED LIGHT ENGINE DAISY 16 LEDs 62mm x 62mm
FWHM / FWTM 64.5° / 92.0°
Efficiency 89 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17484_DAISY-2X2-SHD-WHT-MATT





OPTICAL RESULTS (MEASURED):





LED LIGHT ENGINE DAISY 16 LEDs 62mm x 62mm
FWHM / FWTM 63.5° / 88.5°
Efficiency 78 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C16866_DAISSY-2X2-SHD





LED LIGHT ENGINE DAISY 16 LEDs 62mm x 62mm
FWHM / FWTM 63.5° / 90.0°
Efficiency 90 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17530_DAISSY-2X2-SHD-MET



LED RecLED 62x62mm 1600lm 827-865 36V G1
FWHM / FWTM 65.0° / 92.0°
Efficiency 89 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C17484_DAISSY-2X2-SHD-WHT-MATT



LED RecLED 62x62mm 1600lm 827-865 36V G1
FWHM / FWTM 63.0° / 90.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C17530_DAISSY-2X2-SHD-MET





OPTICAL RESULTS (MEASURED):

MST

Your solutions



LED RecLED 62x62mm 1600lm 827-865 36V G1
FWHM / FWTM 64.0° / 88.0°
Efficiency 76 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C16866_DAISSY-2X2-SHD



MST

Your solutions



LED RecLED 62x62mm 1600lm 827-865 36V G1
FWHM / FWTM 63.5° / 88.0°
Efficiency 75 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C17483_DAISSY-2X2-SHD-MATT



MST

Your solutions



LED RecLED 62x62mm 1600lm 827-865 36V G1
FWHM / FWTM 64.0° / 90.0°
Efficiency 84 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C17536_DAISSY-2X2-SHD-MET-MATT



MST

Your solutions

LED RecLED 62x62mm 1600lm 827-865 36V G1
FWHM / FWTM 65.0° / 93.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour Tunable White
Required components:
C16875_DAISSY-2X2-SHD-WHT





OPTICAL RESULTS (MEASURED):

MST

Your solutions



LED RecLED 62x62mm 1600lm 8x0 36V G1
FWHM / FWTM 64.5° / 90.5°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17530_DAISSY-2X2-SHD-MET



MST

Your solutions



LED RecLED 62x62mm 1600lm 8x0 36V G1
FWHM / FWTM 66.0° / 93.0°
Efficiency 89 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C16875_DAISSY-2X2-SHD-WHT



MST

Your solutions



LED RecLED 62x62mm 1600lm 8x0 36V G1
FWHM / FWTM 64.0° / 91.0°
Efficiency 83 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17536_DAISSY-2X2-SHD-MET-MATT



MST

Your solutions

LED RecLED 62x62mm 1600lm 8x0 36V G1
FWHM / FWTM 64.0° / 88.5°
Efficiency 76 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17483_DAISSY-2X2-SHD-MATT




OPTICAL RESULTS (MEASURED):

MST

Your solutions



LED RecLED 62x62mm 1600lm 8x0 36V G1
FWHM / FWTM 65.5° / 93.0°
Efficiency 89 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C17484_DAISY-2X2-SHD-WHT-MATT



MST



Your solutions

LED RecLED 62x62mm 1600lm 8x0 36V G1
FWHM / FWTM 64.5° / 88.5°
Efficiency 76 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C16866_DAISY-2X2-SHD





NICHIA

LED NF2W757G-MT (Tunable White)
FWHM / FWTM 62.0° / 86.0°
Efficiency 93 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour Tunable White
Required components:
C16875_DAISY-2X2-SHD-WHT



NICHIA



LED NF2W757G-MT (Tunable White)
FWHM / FWTM 61.0° / 84.0°
Efficiency 82 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour Tunable White
Required components:
C16866_DAISY-2X2-SHD



OPTICAL RESULTS (MEASURED):



SAMSUNG

LED LM28xB Series
FWHM / FWTM 60.0° / 83.0°
Efficiency 79 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16866_DAISY-2X2-SHD





SAMSUNG

LED LM28xB Series
FWHM / FWTM 60.0° / 85.0°
Efficiency 79 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C17483_DAISY-2X2-SHD-MATT



SAMSUNG

LED LM28xB Series
FWHM / FWTM 61.0° / 87.0°
Efficiency 89 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16875_DAISY-2X2-SHD-WHT



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)