

DAISY-8X1-M

~35° wide beam

SPECIFICATION:

Dimensions	305.2 x 38.1 mm
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ

MATERIALS:

Component	Type	Material	Colour	Finish	Length
C17819_DAISY-4X1-M-US	Linear lens	PMMA	clear		133.3
C17172_DAISY-8X1-SHD-MATT-WHT	Shade	PC	white	matt	305.3
C17171_DAISY-8X1-SHD-MATT	Shade	PC	black	matt	305.3



ORDERING INFORMATION:


Quantities for one set:

Linear lens	2
Shade	1



Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17819_DAISY-4X1-M-US » Box size: 480 x 280 x 300 mm	Linear lens	504	84	84	6.2
C17172_DAISY-8X1-SHD-MATT-WHT » Box size: 400 x 300 x 300 mm	Shade	84	42	42	4.2
C17171_DAISY-8X1-SHD-MATT » Box size: 400 x 300 x 300 mm	Shade	84	42	42	4.0






See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (SIMULATED):




LED J Series 5050 Round LES
FWHM / FWTM 28.0° / 64.0 + 62.0°
Efficiency 87 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C17171_DAISSY-8X1-SHD-MATT



Light distribution files




LED J Series 5050 Round LES
FWHM / FWTM 26.0° / 59.0 + 60.0°
Efficiency 86 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C17171_DAISSY-8X1-SHD-MATT



Light distribution files



LED LUXEON 5050 Square LES
FWHM / FWTM 28.0° / 63.0 + 66.0°
Efficiency 87 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C17171_DAISSY-8X1-SHD-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON 5050 Square LES
FWHM / FWTM 32.0° / 70.0°
Efficiency 86 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C17171_DAISSY-8X1-SHD-MATT



Light distribution files




LED Duris E 2835
FWHM / FWTM 36.0° / 76.0°
Efficiency 93 %
Peak intensity 1.8 cd/lm
LEDs/each optic 2
Light colour/type White
Required components:
C17171_DAISSY-8X1-SHD-MATT



Light distribution files



LED Duris S8
FWHM / FWTM 32.0 + 34.0° / 70.0 + 72.0°
Efficiency 86 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C17171_DAISSY-8X1-SHD-MATT




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED LH231B
 FWHM / FWTM 20.0° / 39.0 + 38.0°
 Efficiency 86 %
 Peak intensity 4.8 cd/lm
 LEDs/each optic 1
 Light colour/type White

Required components:
 C17171_DAISSY-8X1-SHD-MATT




Light distribution files

SAMSUNG

LED LM28xB Series
 FWHM / FWTM 18.0° / 36.0 + 35.0°
 Efficiency 89 %
 Peak intensity 5.7 cd/lm
 LEDs/each optic 1
 Light colour/type White

Required components:
 C17171_DAISSY-8X1-SHD-MATT




Light distribution files

SAMSUNG

LED LM28xB Series
 FWHM / FWTM 36.0° / 76.0°
 Efficiency 83 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 2
 Light colour/type White

Required components:
 C17171_DAISSY-8X1-SHD-MATT



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)