

HEIDI-RS

~8° spot beam

SPECIFICATION:

Dimensions	Ø 21.6
Height	11.7 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
HEIDI-RS	Single lens	PMMA	clear		
HEIDI-TAPE	Tape	Acryl tape	black		

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA11663_HEIDI-RS	Single lens	3264	204	204	10.4
» Box size: 480 x 280 x 300 mm					



See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):




LED XB-D
FWHM / FWTM 8.0°
Efficiency 91 %
Peak intensity 19.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files




LED XB-H
FWHM / FWTM 10.0° / 19.0°
Efficiency 90 %
Peak intensity 18.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XP-E
FWHM / FWTM 8.0° / 18.0°
Efficiency 93 %
Peak intensity 26.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):




LED XP-E2
 FWHM / FWTM 8.0° / 14.0°
 Efficiency 90 %
 Peak intensity 38 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED XP-G
 FWHM / FWTM 9.0° / 20.0°
 Efficiency 93 %
 Peak intensity 16.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED XP-G2
 FWHM / FWTM 11.0° / 20.0°
 Efficiency 91 %
 Peak intensity 19.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):




LED XQ-E HD
FWHM / FWTM 6.0° / 12.0°
Efficiency 94 %
Peak intensity 42.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XQ-E HI
FWHM / FWTM 5.0° / 11.0°
Efficiency 94 %
Peak intensity 55.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XT-E
FWHM / FWTM 10.0° / 21.0°
Efficiency 97 %
Peak intensity 17.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON C
FWHM / FWTM 7.0° / 14.0°
Efficiency 92 %
Peak intensity 35.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files





LED LUXEON T
FWHM / FWTM 11.0° / 20.0°
Efficiency 92 %
Peak intensity 16.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED LUXEON TX
FWHM / FWTM 10.0° / 20.0°
Efficiency 90 %
Peak intensity 19.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OPTICAL RESULTS (MEASURED):





LED	NCSxx19A
FWHM / FWTM	8.0° / 18.0°
Efficiency	89 %
Peak intensity	19 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files



LED	NCSxx19B
FWHM / FWTM	9.0° / 18.0°
Efficiency	90 %
Peak intensity	25.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files




LED	NVSxx19A
FWHM / FWTM	10.0° / 23.0°
Efficiency	89 %
Peak intensity	13.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

OPTICAL RESULTS (MEASURED):




LED NVSxx19B/NVSxx19C
 FWHM / FWTM 12.0° / 26.0°
 Efficiency 92 %
 Peak intensity 13.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED NVSxx19B/NVSxx19C
 FWHM / FWTM 12.0° / 21.0°
 Efficiency 96 %
 Peak intensity 14.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED OSLON Square CSSRM2/CSSRM3
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 89 %
 Peak intensity 20.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files

OPTICAL RESULTS (MEASURED):


OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM / FWTM 7.0° / 16.0°
Efficiency 93 %
Peak intensity 24.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files

SAMSUNG


LED LH181A
FWHM / FWTM 8.0° / 24.0°
Efficiency 94 %
Peak intensity 14.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

SAMSUNG

LED LH181B
FWHM / FWTM 9.0° / 24.0°
Efficiency 94 %
Peak intensity 15 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED LH351Z
 FWHM / FWTM 11.0° / 19.0°
 Efficiency 89 %
 Peak intensity 20.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED Z5
 FWHM / FWTM 7.0° / 16.0°
 Efficiency 93 %
 Peak intensity 32.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:

Light distribution files



LED Z5M1/Z5M2
 FWHM / FWTM 11.0° / 19.0°
 Efficiency 94 %
 Peak intensity 17.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED XB-D
FWHM / FWTM 8.0° / 18.0°
Efficiency 93 %
Peak intensity 25 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XE-G
FWHM / FWTM 8.0° / 16.0°
Efficiency 97 %
Peak intensity 33.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XE-G
FWHM / FWTM 8.0° / 16.0°
Efficiency 95 %
Peak intensity 29.7 cd/lm
LEDs/each optic 1
Light colour/type Red
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED XHP35.2 HD
FWHM / FWTM 20.0° / 34.0°
Efficiency 91 %
Peak intensity 5.5 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XHP35.2 HI
FWHM / FWTM 16.0° / 29.0°
Efficiency 94 %
Peak intensity 8.7 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XP-E2
FWHM / FWTM 8.0° / 16.0°
Efficiency 96 %
Peak intensity 37.4 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED XP-G4 HI
 FWHM / FWTM 8.0° / 18.0°
 Efficiency 97 %
 Peak intensity 24.8 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED LUXEON CZ
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 96 %
 Peak intensity 48.9 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON HL2X
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 94 %
 Peak intensity 11.1 cd/Im
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON HL2Z
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 95 %
 Peak intensity 19.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED LUXEON MZ
 FWHM / FWTM 18.0° / 31.0°
 Efficiency 95 %
 Peak intensity 7.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON Rubix
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 96 %
 Peak intensity 47.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON Rubix
FWHM / FWTM 6.0° / 14.0°
Efficiency 96 %
Peak intensity 45.6 cd/lm
LEDs/each optic 1
Light colour/type Blue
Required components:



Light distribution files




LED LUXEON Rubix
FWHM / FWTM 6.0° / 14.0°
Efficiency 96 %
Peak intensity 48.4 cd/lm
LEDs/each optic 1
Light colour/type Red
Required components:



Light distribution files



LED LUXEON Rubix
FWHM / FWTM 6.0° / 14.0°
Efficiency 96 %
Peak intensity 46.4 cd/lm
LEDs/each optic 1
Light colour/type Green
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED	LUXEON SunPlus 20 Line (120 deg)
FWHM / FWTM	8.0° / 16.0°
Efficiency	96 %
Peak intensity	30 cd/Im
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files




LED	LUXEON SunPlus 20 Line (150 deg)
FWHM / FWTM	8.0° / 17.0°
Efficiency	91 %
Peak intensity	28.5 cd/Im
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files



LED	LUXEON TX
FWHM / FWTM	10.0° / 20.0°
Efficiency	96 %
Peak intensity	19.6 cd/Im
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON Z
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 95 %
 Peak intensity 51.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files





LED LUXEON Z ES
 FWHM / FWTM 7.7° / 17.0°
 Efficiency 94 %
 Peak intensity 33.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED SST-10-IR-B90
 FWHM / FWTM 8.0° / 16.0°
 Efficiency 95 %
 LEDs/each optic 1
 Light colour/type IR
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED SST-20 Gen1
FWHM / FWTM 10.0° / 19.0°
Efficiency 94 %
Peak intensity 22.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED NFSx757G
FWHM / FWTM 6.0° / 17.0°
Efficiency 96 %
Peak intensity 32.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED NVSW519A
FWHM / FWTM 14.0° / 28.0°
Efficiency 92 %
Peak intensity 9.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED NVSxE21A
 FWHM / FWTM 8.0° / 20.0°
 Efficiency 93 %
 Peak intensity 20.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED NVSxx19B/NVSxx19C
 FWHM / FWTM 12.0° / 22.0°
 Efficiency 94 %
 Peak intensity 14.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED NVSxx19B/NVSxx19C
 FWHM / FWTM 12.0° / 22.0°
 Efficiency 94 %
 Peak intensity 14.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED NVSxx19B/NVSxx19C
 FWHM / FWTM 12.0° / 22.0°
 Efficiency 94 %
 Peak intensity 14.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED OSCONIQ P 3030
 FWHM / FWTM 7.1° / 16.0°
 Efficiency 96 %
 Peak intensity 34.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED OSLON PURE 1010
 FWHM / FWTM 8.0° / 16.0°
 Efficiency 93 %
 Peak intensity 29.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files

OPTICAL RESULTS (SIMULATED):


OSRAM
Opto Semiconductors

LED OSLON Square EC
FWHM / FWTM 12.0°
Efficiency %
Peak intensity 11.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files

OSRAM
Opto Semiconductors


LED OSLON Square Flat
FWHM / FWTM 8.0° / 17.0°
Efficiency 96 %
Peak intensity 30.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM / FWTM 8.0° / 16.0°
Efficiency 96 %
Peak intensity 32.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED SFH 4170S
FWHM / FWTM 6.0° / 14.0°
Efficiency 88 %
LEDs/each optic 1
Light colour/type IR
Required components:



Light distribution files

OSRAM
Opto Semiconductors


LED SFH 4715AS
FWHM / FWTM 10.0° / 20.0°
Efficiency 96 %
LEDs/each optic 1
Light colour/type IR
Required components:



Light distribution files

OSRAM
Opto Semiconductors

LED SFH 4716AS
FWHM / FWTM 8.0° / 15.0°
Efficiency 95 %
LEDs/each optic 1
Light colour/type IR
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LH231B
FWHM / FWTM 11.0° / 24.0°
Efficiency 96 %
Peak intensity 14.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

SAMSUNG


LED LH351B
FWHM / FWTM 12.0° / 22.0°
Efficiency 94 %
Peak intensity 14.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

SAMSUNG

LED LH351C
FWHM / FWTM 12.0° / 24.0°
Efficiency 95 %
Peak intensity 13.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED MGN1108MS
FWHM / FWTM 8.0° / 14.0°
Efficiency 97 %
LEDs/each optic 1
Light colour/type IR
Required components:



Light distribution files



LED MJN1108MS
FWHM / FWTM 8.0° / 14.0°
Efficiency 97 %
LEDs/each optic 1
Light colour/type IR
Required components:



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)