HEKLA-KONNTAKT-I

Version compatible with COBs of 19 x 19 mm packages. The final installation requires two KONNTAKT parts per connector.

SPECIFICATION:

Dimensions	Ø 44.0
Height	5.7 mm
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
L20752_HEKLA-KONNTAKT-I » Box size: 285 x 190 x 205 mm	500	250	250	3.1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



GENERAL INFORMATION	
RATED VOLTAGE/CURRENT	VDE 80VDC/3A UL 60VDC/100W
ELECTRICAL REQUIREMENTS	IEC 60838-1
WIRES FOR PUSH-IN TERMINALS	STRANDED TINNED WIRES (0,35mm2 - 0,75mm2) AWG18-22 SOLID WIRES (0,5mm2) AWG20
WIRE STRIP LENGTH	7 +1 mm
FASTENING	SCREWS 2XM3, Screw hole distance 35mm
MAX. SCREW FIXING TORQUE	0,5Nm
MAX. TIM THICKNESS	0,25mm, recommended to use without
RATED TEMPERATURE	120°C



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 7
FI-24100 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.