

PRODUCT FAMILY DATASHEET HEKLA-CONNECTOR

KONNTAKT

LEDiLs standard solderless connector and socket range compatible with a wide range of our lenses and reflectors

Ø44 mm LEDiL HEKLA sockets and solderless connectors. Support for many different size COBs and a variety of LEDiL optics with Zhaga mounting holes. Easy to use twist and lock mechanism for quick optics assembly and replacement. Long lasting materials that can handle high temperatures without losing grip.

HEKLA-CONNECTOR

Ø44 mm solderless connectors compatible with many different size COBs up to 17 mm LES sizes



PRODUCTS:

FP15501_HEKLA-C

FP15500_HEKLA-B

FP15490_HEKLA-A

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 13.5 x 13.5 mm packages and max 11.6 mm LES size

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 17.85 x 17.85 mm packages and max 14.2 mm LES size

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 12.5 x 12.5 mm packages and max 9 mm LES size



PRODUCT FAMILY DATASHEET HEKLA-CONNECTOR

PRODUCTS:

FP15957_HEKLA-J

FP15949_HEKLA-I

FP15948_HEKLA-H

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 13.35 x 13.35 mm packages and max 7.5 mm LES size

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 19 x 19 mm packages and max 17 mm LES size

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 16 x 19 mm packages and max 14 mm LES size

FP15947_HEKLA-G

FP15503_HEKLA-E

FP15502_HEKLA-D

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 12 x 15 mm packages and max 10 mm LES size

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm Version compatible with COBs of 15.8 x

15.8 mm packages and max 14.3 mm LES size

Dimensions: 44.0 mm x 44.0 mm Height: 5.50 mm

Version compatible with COBs of 15.85 x 15.85 mm packages and max 10.7 mm LES size



PRODUCT FAMILY DATASHEET HEKLA-CONNECTOR

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy