

DATE
29.02.2024

NOTE. Only one round hole in each PCB

Wire connector solder
pad center points
WAGO 2065
8mmx2,3mm, 2,7 mm
height

72 LED center points
15.55 ± 0.1

279.9 ± 0.1 c/c
Position pin holes

Screw hole for
PCB attachment

139.95 ± 0.1

7.775

7.4

14.8 ± 0.1

30 ± 0.1

∅ 2 ± 0.1

∅ 3.3


Keep out areas

Front view
Scale: 1:1

557 ± 0.2

Front view
Scale: 1:2

LED 1 X 2835
90° rotation

| | | |
|---|--|---|
| MECHANICAL DRAWING | | LEDiL |
| PRODUCT LIANNA-2R 2ft_30mm_PCB reference | | |
| Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing. | FIRST ANGLE PROJECTION:  | This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy. |
| SCALE 1:1 | WEIGHT - | |
| | | A3 SHEET 1/1 |