

PRODUCT DATASHEET CA11136_LO2-W

LO2-W

~40° wide beam optimized for Osram Golden Dragon+. 13.9 mm high assembly with installation tape.

SPECIFICATION:

Dimensions	Ø 21.6 mm
Height	13.9 mm
Fastening	tape
ROHS compliant	yes 🛈



MATERIALS:

Component	
LO2-W	
LO3-LH1-TAPE	
LEILA-TAPE	


Туре	Material	Colour	Finish	Length (mm)
Single lens	PMMA	clear		
Holder	PC	black		
Таре	PU tape 0,2	5nbhack		

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA11136_LO2-W	2880		180	13.4
» Box size: 480 x 280 x 300 mm				



PRODUCT DATASHEET CA11136_LO2-W



See also our general installation guide: <u>www.ledil.com/installation_guide</u>



OPTICAL RESULTS (MEASURED):

LED Golden Dragon+ FWHM / FWTM 44.0° Efficiency % LEDs/each optic 1 Light colour/type White Required components:	44.0°			
Efficiency % LEDs/each optic 1 Light colour/type White				
LEDs/each optic 1 Light colour/type White	%			
Light colour/type White				
	1			
Required components:	White			
	s:			
			Light distribution files	
	١	Vhite	Vhite	Vhite



OPTICAL RESULTS (SIMULATED):

			94° 78°
LED FWHM / FWTM	XHP50.3 HI 34.0° / 72.0°		ada
Efficiency	88 %		
Peak intensity	1.9 cd/lm		est* 1230
LEDs/each optic	1		
Light colour/type	White		100
Required components:			1940 - 1962 - 1962 - 1962
		Light distrib	ution files



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Poznan, Poland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy

Last update: 13/05/2024 Subject to change without prior notice LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.