

## G2-LXP2-M

~20° medium beam with light, black holder.  
Assembly with installation tape.

## SPECIFICATION:

Dimensions	Ø 21.8
Height	14.7 mm
Fastening	tape
ROHS compliant	yes ⓘ




## MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
LXP2-M	Single lens	PMMA	clear		
LXP2-LT-HLD	Holder	PC	black		
HEIDI-TAPE	Tape	Acrylic foam	black		

## ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA14510_G2-LXP2-M	1680	336	112	8.0
» Box size: 480 x 280 x 300 mm				




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

## OPTICAL RESULTS (MEASURED):



LED	XP-E
FWHM / FWTM	22.0° / 40.0°
Efficiency	88 %
Peak intensity	5.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED XD16  
 FWHM / FWTM 26.0° / 49.0°  
 Efficiency 86 %  
 Peak intensity 3.4 cd/lm  
 LEDs/each optic 2  
 Light colour/type White  
 Required components:



Light distribution files




LED XP-G2  
 FWHM / FWTM 25.0° / 42.0°  
 Efficiency 94 %  
 Peak intensity 4.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED XP-G2 HE  
 FWHM / FWTM 26.0° / 45.0°  
 Efficiency 90 %  
 Peak intensity 4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED XQ-E HI  
FWHM / FWTM 26.0° / 46.0°  
Efficiency 90 %  
Peak intensity 3.9 cd/Im  
LEDs/each optic 2  
Light colour/type White  
Required components:



Light distribution files




LED XT-E  
FWHM / FWTM 26.0° / 43.0°  
Efficiency 90 %  
Peak intensity 4.3 cd/Im  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED SST-10-B130  
FWHM / FWTM 25.0° / 42.0°  
Efficiency 92 %  
LEDs/each optic 1  
Light colour/type IR  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED NVSxE21A  
 FWHM / FWTM 26.0° / 45.0°  
 Efficiency 88 %  
 Peak intensity 4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED NVSxx19B/NVSxx19C  
 FWHM / FWTM 25.0° / 44.0°  
 Efficiency 87 %  
 Peak intensity 4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED LH351A  
 FWHM / FWTM 25.0° / 41.0°  
 Efficiency 41 %  
 Peak intensity 4.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

#### SAMSUNG


LED LH351B  
 FWHM / FWTM 25.0° / 41.0°  
 Efficiency 90 %  
 Peak intensity 4.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED Z5M1/Z5M2  
 FWHM / FWTM 24.0° / 40.0°  
 Efficiency 92 %  
 Peak intensity 4.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED Z5P  
 FWHM / FWTM 26.0° / 41.0°  
 Efficiency 91 %  
 Peak intensity 4.4 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)