

LEILA-Y-O

~45° + 15° oval beam. 14.8 mm high assembly with holder, installation tape and pins.

SPECIFICATION:

Dimensions	Ã~ 21.6
Height	14.8 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish	Length
LEILA-Y-O	Single lens	PMMA	clear	gloss	20.0
LEILA-Y-HLD	Holder	PC	black	gloss	21.6
LEILA-Y-TAPE	Tape	Acrylic foam			18.0

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA18094_LEILA-Y-O » Box size: 476 x 273 x 197 mm	1800	180	180	7.6




See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):




LED XHP35 HI
FWHM / FWTM 49.0 + 16.0° / 70.0 + 31.0°
Efficiency 80 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files





LED XP-G4
FWHM / FWTM 50.0 + 14.0° / 69.0 + 29.0°
Efficiency 81 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED NVSW719AC
FWHM / FWTM 50.0 + 14.0° / 68.0 + 28.0°
Efficiency 81 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





Light distribution files

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED OSLON Pure 1414
FWHM / FWTM 44.0 + 18.0° / 72.0 + 34.0°
Efficiency 78 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED J Series 3030C
FWHM / FWTM 50.0 + 14.0° / 70.0 + 26.0°
Efficiency 81 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED J Series 5050 Round LES
FWHM / FWTM 20.0 + 44.0°
Efficiency 78 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED J Series 5050B 6V K Class
FWHM / FWTM 46.0 + 20.0° / 74.0 + 42.0°
Efficiency 77 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




OPTICAL RESULTS (SIMULATED):




LED XHP35.2 HI
FWHM / FWTM 49.0 + 18.0° / 74.0 + 34.0°
Efficiency 78 %
Peak intensity 2.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



LED XM-L RGBW (XMLDCL HD)
FWHM / FWTM 48.0 + 22.0° / 78.0 + 38.0°
Efficiency 79 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type RGBW
Required components:



LED XM-L2
FWHM / FWTM 17.0 + 47.0°
Efficiency 81 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED XM-L3
FWHM / FWTM 17.0 + 48.0°
Efficiency 76 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XP-E2
FWHM / FWTM 10.0 + 49.0°
Efficiency 85 %
Peak intensity 4.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XP-G2
FWHM / FWTM 13.0 + 49.0°
Efficiency 84 %
Peak intensity 3.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED XP-G3
 FWHM / FWTM 15.0 + 48.0°
 Efficiency 80 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED XP-L2
 FWHM / FWTM 18.0 + 47.0°
 Efficiency 77 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files



LED XQ-E HD
 FWHM / FWTM 51.0 + 16.0° / 72.0 + 29.0°
 Efficiency 82 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 2
 Light colour/type White
 Required components:



Detector Image: 11 luminance
 20-2-2024
 Zemax OptiX 21.3




Light distribution files


OPTICAL RESULTS (SIMULATED):



LED XQ-E HI
 FWHM / FWTM 52.0 + 18.0° / 72.0 + 28.0°
 Efficiency 82 %
 Peak intensity 2.6 cd/lm
 LEDs/each optic 2
 Light colour/type White
 Required components:




Detector Image: 11 luximance
 28.2.2024
 Zemax OptiX Classic 21.3



Light distribution files




LED LUXEON 5050 Round LES
 FWHM / FWTM 21.0 + 44.0°
 Efficiency 78 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED LUXEON 5050 Square LES
 FWHM / FWTM 21.0 + 44.0°
 Efficiency 78 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON MZ
FWHM / FWTM 17.0 + 43.0°
Efficiency 78 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED LUXEON TX
FWHM / FWTM 13.0 + 48.0°
Efficiency 82 %
Peak intensity 3.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED NCSxE17A
FWHM / FWTM 44.0 + 20.0° / 74.0 + 40.0°
Efficiency 72 %
Peak intensity 2 cd/lm
LEDs/each optic 4
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):





LED NCSxE17A
 FWHM / FWTM 44.0 + 20.0° / 74.0 + 39.0°
 Efficiency 73 %
 Peak intensity 2 cd/lm
 LEDs/each optic 4
 Light colour/type RGBW
 Required components:



Light distribution files




LED NCSxE17A
 FWHM / FWTM 45.0 + 21.0° / 74.0 + 40.0°
 Efficiency 70 %
 Peak intensity 1.8 cd/lm
 LEDs/each optic 4
 Light colour/type RGBW
 Required components:



Light distribution files





LED NV4x144A
 FWHM / FWTM 46.0 + 24.0° / 78.0 + 42.0°
 Efficiency 69 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files


OPTICAL RESULTS (SIMULATED):



OPTICAL RESULTS (SIMULATED):


OSRAM
Opto Semiconductors

LED OSCONIQ S 5050
 FWHM / FWTM 47.0 + 22.0° / 76.0 + 43.0°
 Efficiency 76 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:





OSRAM
Opto Semiconductors

LED OSLON Pure 1414
 FWHM / FWTM 52.0 + 10.0° / 66.0 + 20.0°
 Efficiency 84 %
 Peak intensity 4.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



OSRAM
Opto Semiconductors

LED OSLON SSL 150
 FWHM / FWTM 10.0 + 49.0°
 Efficiency 84 %
 Peak intensity 4.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):


OSRAM
Opto Semiconductors

LED SYNIOS S2222
FWHM / FWTM 48.0 + 8.0° / 65.0 + 20.0°
Efficiency 83 %
Peak intensity 5 cd/lm
LEDs/each optic 1
Light colour/type Red
Required components:




OSRAM
Opto Semiconductors

LED SYNIOS S2222
FWHM / FWTM 50.0 + 10.0° / 67.0 + 20.0°
Efficiency 82 %
Peak intensity 4.4 cd/lm
LEDs/each optic 1
Light colour/type Blue
Required components:



OSRAM
Opto Semiconductors


LED SYNIOS S2222
FWHM / FWTM 50.0 + 8.0° / 66.0 + 20.0°
Efficiency 83 %
Peak intensity 5 cd/lm
LEDs/each optic 1
Light colour/type Yellow
Required components:



OPTICAL RESULTS (SIMULATED):


OSRAM
Opto Semiconductors

LED SYNIOS S2222
FWHM / FWTM 50.0 + 9.0° / 67.0 + 20.0°
Efficiency 83 %
Peak intensity 4.5 cd/lm
LEDs/each optic 1
Light colour/type Blue
Required components:




OSRAM
Opto Semiconductors

LED SYNIOS S2222
FWHM / FWTM 50.0 + 8.0° / 66.0 + 20.0°
Efficiency 83 %
Peak intensity 4.4 cd/lm
LEDs/each optic 1
Light colour/type Green
Required components:




SAMSUNG

LED LH351B
FWHM / FWTM 15.0 + 49.0°
Efficiency 81 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OPTICAL RESULTS (SIMULATED):

 SEUL SEMICONDUCTOR	
LED	Z5M4
FWHM / FWTM	48.0 + 16.0° / 72.0 + 30.0°
Efficiency	81 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)