

LEILA


Lenses for general, wall-washing and sports lighting

LEDiL's well-established LEILA family with symmetric and asymmetric beams. LEILA-G2 comes with a thinner holder design and is backwards compatible with previous generations. The wall-washing beam is designed to be used in groups to provide uniform illumination with a typical installation distance from the wall of 10-20 cm and optimal luminaire spacing of 5-15 cm.



PRODUCTS:


CA14507_G2-LXP2-D-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~14° diffused spot beam with light, black holder. Assembly with location pins and installation tape.


CA18988_LEILA-Y-RS-HLD2-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° spot beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins. White version.

CP11631_LXP3-RS




Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly.

PRODUCTS:


CA18486_LEILA-Y-WW-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~55° wide beam. 14.8 mm high assembly with holder, installation tape and pins. White version.


FA10832_LXP-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA12666_LXB2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~25° medium beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


CA18089_LEILA-Y-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° spot beam. 14.8 mm high assembly with holder, installation tape and pins.


FA10696_LN2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 13.50 mm

~9.6° spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

CP19455_LEILA-Y-SC2-M-WHT




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam. Assembly with white SC2-holder.

PRODUCTS:


CA12394_LR2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~40° wide beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


CA14512_G2-LXP2-O-90



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.
Variant with beam direction rotated 90°. Variant with thin holder.


FA10613_LM1-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~20° spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


CA18993_LEILA-Y-O-HLD2-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~45° + 15° oval beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins. White version


CA11930_LR2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° diffused spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

CA18974_LEILA-Y-M-HLD2




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins.

PRODUCTS:


CA11481_LXP2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA14392_LXP2-O-WAS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

Asymmetric beam for wall-washing and optimized for CREE XP-E. 14.6 mm high assembly with installation tape.


CA18094_LEILA-Y-O



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~45° + 15° oval beam. 14.8 mm high assembly with holder, installation tape and pins.


FA10753_LO2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~14° diffused spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.


CP12415_LOS-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~10° x 40° oval beam optimized for Osram Oslon Square EC. 14.3 mm high assembly. Variant with beam direction rotated 90°.

CP17589_LEILA-SC-M




Dimensions: 21.6 mm x 21.6 mm
Height: 14.90 mm

~25° wide beam

PRODUCTS:


FA10660_LXP-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP19442_LEILA-Y-SC2-WW



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~55° wide beam. Assembly with black SC2-holder.


CA12263_LR2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.40 mm

~14° diffused spot beam optimized for LUXEON Rebel. 14.4 mm high assembly with installation tape.


CA14508_G2-LXP2-D



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~14° diffused spot beam with light, black holder. Assembly with installation tape.


CA18989_LEILA-Y-SS-HLD2-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° smooth spot beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins. White version.

CP11632_LXP3-D




Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly.

PRODUCTS:


CA18487_LEILA-Y-O-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~45° + 15° oval beam. 14.8 mm high assembly with holder, installation tape and pins. White version


LR1-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~40° wide beam optimized for LUXEON Rebel. 14.3 mm high assembly.


CA12667_LXB2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~40° wide beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.


CA18090_LEILA-Y-SS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° smooth spot beam. 14.8 mm high assembly with holder, installation tape and pins.


FA10697_LN2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 13.50 mm

~25° medium beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

CP19456_LEILA-Y-SC2-W-WHT




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~36° wide beam. Assembly with white SC2-holder.

PRODUCTS:


CP12395_LXP3-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly.


CA15772_G2-LXP2-W-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~40° wide beam with light, black holder. Assembly with location pins and installation tape.


FA10614_LM1-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~25° medium beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


CP19438_LEILA-Y-SC2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° spot beam. Assembly with black SC2-holder.


CA11931_LR2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

CA14503_G2-LXP2-RS-P




Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with thin holder with pins.

PRODUCTS:


CA18976_LEILA-Y-W-HLD2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~36° wide beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins.


CA11482_LXP2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

CA18483_LEILA-Y-RS-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm


~10° spot beam. 14.8 mm high assembly with holder, installation tape and pins. White version.

LE1-M

Dimensions: 21.6 mm x 21.6 mm
Height: 15.10 mm

~25° medium beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.


CP12416_LOS-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~40° wide beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

CP17590_LEILA-SC-O-90




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° x 40° oval beam

PRODUCTS:


FA10661_LXP-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP19443_LEILA-Y-SC2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~45° + 15° oval beam. Assembly with black SC2-holder.


CA12264_LR2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.40 mm

~25° medium beam optimized for LUXEON Rebel. 14.4 mm high assembly with installation tape.


CA14509_G2-LXP2-M-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~20° medium beam with light, black holder. Assembly with location pins and installation tape.


CA18990_LEILA-Y-M-HLD2-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins. White version.

FA11739_LXP-RS2




Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

PRODUCTS:


CA18488_LEILA-Y-M-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam. 14.8 mm high assembly with holder, installation tape and pins. White version.


FA11116_LXP-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA12816_LXP2-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA18091_LEILA-Y-M



Dimensions: 21.6 mm x 21.0 mm
Height: 14.80 mm

~25° medium beam. 14.8 mm high assembly with holder, installation tape and pins.


FA10698_LN2-REC



Dimensions: 21.6 mm x 21.6 mm
Height: 13.50 mm

~35° x 25° rectangular beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

CP19457_LEILA-Y-SC2-WW-WHT




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~55° wide beam. Assembly with white SC2-holder.

PRODUCTS:


CP12412_LOS-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~9.6° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


CA16435_LXP2-SS-WAS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.72 mm

Asymmetric beam. Assembly with installation tape.


FA10650_LM1-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~14° diffused spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


CP19439_LEILA-Y-SC2-SS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° smooth spot beam. Assembly with black SC2-holder.


FA11937_LXM-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~9.6° spot beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.

CA14505_G2-LXP2-RS2-P




Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~8.5° spot beam with light, black holder. Assembly with location pins and installation tape.

PRODUCTS:


CA18977_LEILA-Y-WW-HLD2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~55° wide beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins.


CA11483_LXP2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA18484_LEILA-Y-SS-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° smooth spot beam. 14.8 mm high assembly with holder, installation tape and pins. White version.


LE1-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 15.10 mm

~9.6° spot beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.


CA12629_LR2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° x 40° oval beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.
Variant with beam direction rotated 90°.

CP17591_LEILA-SC-W




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~40° wide beam

PRODUCTS:


FA10663_LXP-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP19453_LEILA-Y-SC2-RS-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° spot beam. Assembly with white SC2-holder


CA12392_LXP2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CA14510_G2-LXP2-M



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~20° medium beam with light, black holder. Assembly with installation tape.


CA18991_LEILA-Y-W-HLD2-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~36° wide beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins. White version.

FA11894_LM1-W




Dimensions: 21.6 mm x 21.6 mm
Height: 14.04 mm

~40° wide beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.

PRODUCTS:


CA18972_LEILA-Y-RS-HLD2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~10° spot beam. 14.8 mm high assembly with star pcb-holder, installation tape and pins.


CA11136_LO2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 13.90 mm

~40° wide beam optimized for Osram Golden Dragon+. 13.9 mm high assembly with installation tape.


CP12817_LXP3-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly.


CA18092_LEILA-Y-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~36° wide beam. 14.8 mm high assembly with holder, installation tape and pins.


FA10750_LO2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~25° medium beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

CP19458_LEILA-Y-SC2-O-90-WHT




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~45° + 15° oval beam. Assembly with white SC2-holder.

PRODUCTS:


CP12413_LOS-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~14° diffused spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


CP17587_LEILA-SC-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~9.6° spot beam


FA10652_LC1-M



Dimensions: 21.6 mm x 21.6 mm
Height: 16.50 mm

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.


CP19440_LEILA-Y-SC2-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam. Assembly with black SC2-holder.


FA11939_LXM-M



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~25° medium beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.

CA14506_G2-LXP2-RS2




Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~8.5° spot beam with light, black holder. Assembly with installation tape.

PRODUCTS:


CA18978_LEILA-Y-O-HLD2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~45° + 15° oval beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins.


CA11484_LXP2-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with beam direction rotated 90°.


CA18485_LEILA-Y-W-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~36° wide beam. 14.8 mm high assembly with holder, installation tape and pins. White version.


LR1-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~14° diffused spot beam optimized for LUXEON Rebel. 14.3 mm high assembly.


CA12665_LXB2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~14° diffused spot beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.

CP17592_LEILA-SC-O-WAS




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

Asymmetric beam for wall-washing

PRODUCTS:


FA10695_LN2-D



Dimensions: 21.6 mm x 21.6 mm
Height: 13.50 mm

~14° diffused spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.


CP19454_LEILA-Y-SC2-SS-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° smooth spot beam. Assembly with white SC2-holder.


CA12393_LR2-W



Dimensions: 21.6 mm x 21.6 mm
Height: 14.50 mm

~40° wide beam optimized for LUXEON Rebel. 14.5 mm high assembly with installation tape.


CA14511_G2-LXP2-O-90-P



Dimensions: 21.8 mm x 21.8 mm
Height: 14.70 mm

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.
Variant with beam direction rotated 90°. Variant with thin holder with pins.


CA18992_LEILA-Y-WW-HLD2-WHT



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~55° wide beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins. White version.

CA11929_LR2-RS




Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~9.6° spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

PRODUCTS:


CA18973_LEILA-Y-SS-HLD2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~14° smooth spot beam. 14.8 mm high assembly with star-pcb holder, installation tape and pins.


FA11450_LXP-M2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.70 mm

~30° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


CP13059_LOS-RS2



Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~8.5° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


CA18093_LEILA-Y-WW



Dimensions: 21.6 mm x 21.6 mm
Height: 14.80 mm

~55° wide beam. 14.8 mm high assembly with holder, installation tape and pins.


FA10751_LO2-RS



Dimensions: 21.6 mm x 21.6 mm
Height: 14.60 mm

~9.6° spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

CP12414_LOS-M




Dimensions: 21.6 mm x 21.6 mm
Height: 14.30 mm

~25° medium beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

PRODUCTS:

CP17588_LEILA-SC-D




Dimensions: 21.6 mm x 21.6 mm

Height: 14.80 mm

~14° diffused spot beam

FA10653_LC1-RS




Dimensions: 21.6 mm x 21.6 mm

Height: 16.50 mm

~9.6° spot beam optimized for
CREE XR-E. 16.5 mm high
assembly with installation tape.

CP19441_LEILA-Y-SC2-W




Dimensions: 21.6 mm x 21.6 mm

Height: 14.80 mm

~36° wide beam. Assembly with
black SC2-holder.

CA12262_LR2-RS



Dimensions: 21.6 mm x 21.6 mm

Height: 14.30 mm

~9.6° spot beam optimized for
LUXEON Rebel. 14.3 mm high
assembly with installation tape.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)