

### LEILA


#### Lenses for general, wall-washing and sports lighting

LEDiL's well-established LEILA family with symmetric and asymmetric beams. LEILA-G2 comes with a thinner holder design and is backwards compatible with previous generations. The wall-washing beam is designed to be used in groups to provide uniform illumination with a typical installation distance from the wall of 10-20 cm and optimal luminaire spacing of 5-15 cm.



#### PRODUCTS:

##### CA18988\_LEILA-Y-RS-HLD2-WHT




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.80 mm**

~10° spot beam. 14.8 mm high assembly with white star-pcb holder, installation tape and pins.

##### CP11631\_LXP3-RS




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly.

##### LP20048\_LEILA-SC2-O-90-WHT




**Dimensions: mm x mm**

**Height: mm**

~45° + 15° oval beam. Variant with beam direction rotated 90°. White version.

### PRODUCTS:


#### CA14507\_G2-LXP2-D-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~14° diffused spot beam with light, black holder. Assembly with location pins and installation tape.


#### CA18486\_LEILA-Y-WW-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~55° wide beam. 14.8 mm high assembly with white holder, installation tape and pins.


#### LE1-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 15.10 mm**

~9.6° spot beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.


#### LP20039\_LEILA-SC2-O-90-WAS



**Dimensions: mm x mm**  
**Height: mm**

Asymmetric beam for wall-washing. Assembly with black SC2-holder.


#### CA12666\_LXB2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~25° medium beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.

#### FA10663\_LXP-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


### PRODUCTS:

#### CP19455\_LEILA-Y-SC2-M-WHT




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~25° medium beam. Assembly with white SC2-holder.

#### CA12394\_LR2-W




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~40° wide beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

#### CA18089\_LEILA-Y-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~10° spot beam. 14.8 mm high assembly with black holder, installation tape and pins.

#### CA18993\_LEILA-Y-O-HLD2-WHT




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~45° + 15° oval beam. 14.8 mm high assembly with white star-pcb holder, installation tape and pins.

#### CA11930\_LR2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~14° diffused spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


#### CA14512\_G2-LXP2-O-90



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**  
 ~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with beam direction rotated 90°. Variant with thin holder.

### PRODUCTS:


#### CA18974\_LEILA-Y-M-HLD2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~25° medium beam. 14.8 mm high assembly with black star-pcb holder, installation tape and pins.


#### CA11481\_LXP2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### LP20044\_LEILA-SC2-M-WHT



**Dimensions: mm x mm**  
**Height: mm**

~25° wide beam. Assembly with white SC2-holder.


#### CA14392\_LXP2-O-WAS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

Asymmetric beam for wall-washing and optimized for CREE XP-E. 14.6 mm high assembly with installation tape.


#### CA18094\_LEILA-Y-O



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~45° + 15° oval beam. 14.8 mm high assembly with black holder, installation tape and pins.

#### FA10750\_LO2-M




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~25° medium beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

### PRODUCTS:

#### LP20035\_LEILA-SC2-D




**Dimensions: mm x mm**

**Height: mm**

~14° diffused spot beam. Assembly with black SC2-holder.

#### CP12415\_LOS-O-90




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.30 mm**

~10° x 40° oval beam optimized for Osram Oslon Square EC. 14.3 mm high assembly. Variant with beam direction rotated 90°.

#### FA10652\_LC1-M




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 16.50 mm**

~25° medium beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.

#### CP19442\_LEILA-Y-SC2-WW




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.80 mm**

~55° wide beam. Assembly with black SC2-holder.

#### CA12263\_LR2-D




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.40 mm**

~14° diffused spot beam optimized for LUXEON Rebel. 14.4 mm high assembly with installation tape.

#### CP17589\_LEILA-SC-M




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.90 mm**

~25° wide beam

### PRODUCTS:


#### CA18989\_LEILA-Y-SS-HLD2-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° smooth spot beam. 14.8 mm high assembly with white star-pcb holder, installation tape and pins.


#### CP11632\_LXP3-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly.


#### LP20049\_LEILA-SC2-OW-90-WHT



**Dimensions: mm x mm**  
**Height: mm**

~50° + 30° oval beam. Variant with beam direction rotated 90°. Assembly with white SC2-holder.


#### CA14508\_G2-LXP2-D



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~14° diffused spot beam with light, black holder. Assembly with installation tape.


#### CA18487\_LEILA-Y-O-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~45° + 15° oval beam. 14.8 mm high assembly with white holder, installation tape and pins.

#### FA10832\_LXP-W




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

### PRODUCTS:

#### LP20040\_LEILA-SC2-O-90




**Dimensions: mm x mm**

**Height: mm**

~45° + 15° oval beam. Variant with beam direction rotated 90°.

Assembly with black SC2-holder.

#### CA12667\_LXB2-W




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.60 mm**

~40° wide beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.

#### FA10695\_LN2-D




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 13.50 mm**

~14° diffused spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

#### CP19456\_LEILA-Y-SC2-W-WHT




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.80 mm**

~36° wide beam. Assembly with white SC2-holder.

#### CP12395\_LXP3-W




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.70 mm**

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly.

#### CA18090\_LEILA-Y-SS




**Dimensions: 21.6 mm x 21.6 mm**

**Height: 14.80 mm**

~14° smooth spot beam. 14.8 mm high assembly with black holder, installation tape and pins.

### PRODUCTS:


#### CP19438\_LEILA-Y-SC2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~10° spot beam. Assembly with black SC2-holder.


#### CA11931\_LR2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~25° medium beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.


#### CA15772\_G2-LXP2-W-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~40° wide beam with light, black holder. Assembly with location pins and installation tape.


#### CA18976\_LEILA-Y-W-HLD2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~36° wide beam. 14.8 mm high assembly with black star-pcb holder, installation tape and pins.


#### CA11482\_LXP2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

#### LP20045\_LEILA-SC2-W-WHT




**Dimensions: mm x mm**  
**Height: mm**

~40° wide beam. Assembly with white SC2-holder.

### PRODUCTS:


#### CA14503\_G2-LXP2-RS-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with thin holder with pins.


#### CA18483\_LEILA-Y-RS-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~10° spot beam. 14.8 mm high assembly with white holder, installation tape and pins.


#### FA10751\_LO2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~9.6° spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.


#### LP20036\_LEILA-SC2-M



**Dimensions: mm x mm**  
**Height: mm**

~25° wide beam. Assembly with black SC2-holder.


#### CP12416\_LOS-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~40° wide beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.

#### FA10653\_LC1-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 16.50 mm**

~9.6° spot beam optimized for CREE XR-E. 16.5 mm high assembly with installation tape.


### PRODUCTS:

**CP19443\_LEILA-Y-SC2-O-90**




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~45° + 15° oval beam. Assembly with black SC2-holder.

**CA12264\_LR2-M**




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.40 mm**  
 ~25° medium beam optimized for LUXEON Rebel. 14.4 mm high assembly with installation tape.

**CP17590\_LEILA-SC-O-90**




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~10° x 40° oval beam

**CA18990\_LEILA-Y-M-HLD2-WHT**




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
 ~25° medium beam. 14.8 mm high assembly with white star-pcb holder, installation tape and pins.

**FA11739\_LXP-RS2**



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**  
 ~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


**CA14509\_G2-LXP2-M-P**



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**  
 ~20° medium beam with light, black holder. Assembly with location pins and installation tape.

### PRODUCTS:


#### CA18488\_LEILA-Y-M-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~25° medium beam. 14.8 mm high assembly with white holder, installation tape and pins.


#### FA11116\_LXP-O-90



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### LP20041\_LEILA-SC2-OW-90



**Dimensions: mm x mm**  
**Height: mm**

~50° + 30° oval beam. Variant with beam direction rotated 90°. Assembly with black SC2-holder.


#### CA12816\_LXP2-RS2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### FA10696\_LN2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~9.6° spot beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

#### CP19457\_LEILA-Y-SC2-WW-WHT




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~55° wide beam. Assembly with white SC2-holder.

### PRODUCTS:


#### CP12412\_LOS-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~9.6° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


#### CA18091\_LEILA-Y-M



**Dimensions: 21.6 mm x 21.0 mm**  
**Height: 14.80 mm**

~25° medium beam. 14.8 mm high assembly with black holder, installation tape and pins.


#### FA10613\_LM1-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~20° spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


#### CP19439\_LEILA-Y-SC2-SS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° smooth spot beam. Assembly with black SC2-holder.


#### FA11937\_LXM-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~9.6° spot beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.

#### CA16435\_LXP2-SS-WAS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.72 mm**

Asymmetric beam. Assembly with installation tape.

### PRODUCTS:


#### CA18977\_LEILA-Y-WW-HLD2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~55° wide beam. 14.8 mm high assembly with black star-pcb holder, installation tape and pins.


#### CA11483\_LXP2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### LP20046\_LEILA-SC2-WW-WHT



**Dimensions: mm x mm**  
**Height: mm**

~50° wide beam. Assembly with white SC2-holder.


#### CA14505\_G2-LXP2-RS2-P



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~8.5° spot beam with light, black holder. Assembly with location pins and installation tape.


#### CA18484\_LEILA-Y-SS-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° smooth spot beam. 14.8 mm high assembly with white holder, installation tape and pins.

#### FA10753\_LO2-D




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~14° diffused spot beam optimized for Osram Golden Dragon+. 14.6 mm high assembly with installation tape.

### PRODUCTS:

#### LP20037\_LEILA-SC2-W




**Dimensions:** mm x mm

**Height:** mm

~40° wide beam. Assembly with black SC2-holder.

#### CA12629\_LR2-O-90




**Dimensions:** 21.6 mm x 21.6 mm

**Height:** 14.80 mm

~10° x 40° oval beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape. Variant with beam direction rotated 90°.

#### FA10660\_LXP-M




**Dimensions:** 21.6 mm x 21.6 mm

**Height:** 14.70 mm

~25° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

#### CP19453\_LEILA-Y-SC2-RS-WHT




**Dimensions:** 21.6 mm x 21.6 mm

**Height:** 14.80 mm

~10° spot beam. Assembly with white SC2-holder.

#### CA12392\_LXP2-W




**Dimensions:** 21.6 mm x 21.6 mm

**Height:** 14.70 mm

~40° wide beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

#### CP17591\_LEILA-SC-W




**Dimensions:** 21.6 mm x 21.6 mm

**Height:** 14.80 mm

~40° wide beam

### PRODUCTS:


#### CA18991\_LEILA-Y-W-HLD2-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~36° wide beam. 14.8 mm high assembly with white star-pcb holder, installation tape and pins.


#### FA11894\_LM1-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~40° wide beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


#### CA14510\_G2-LXP2-M



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~20° medium beam with light, black holder. Assembly with installation tape.


#### CA18972\_LEILA-Y-RS-HLD2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~10° spot beam. 14.8 mm high assembly with black star pcb-holder, installation tape and pins.


#### CA11136\_LO2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.90 mm**

~40° wide beam optimized for Osram Golden Dragon+. 13.9 mm high assembly with installation tape.

#### LP20042\_LEILA-SC2-RS-WHT




**Dimensions: mm x mm**  
**Height: mm**

~9.6° spot beam. Assembly with white SC2-holder.

### PRODUCTS:


#### CP12817\_LXP3-RS2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~8.5° spot beam optimized for  
CREE XP-E. 14.7 mm high  
assembly.


#### FA10697\_LN2-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~25° medium beam optimized for  
Nichia NS6x83. 13.3 mm high  
assembly with installation tape.


#### CP19458\_LEILA-Y-SC2-O-90-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~45° + 15° oval beam. Assembly  
with white SC2-holder.


#### CP12413\_LOS-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~14° diffused spot beam optimized  
for Osram Oslon Square EC. 14.3  
mm high assembly.


#### CA18092\_LEILA-Y-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~36° wide beam. 14.8 mm high  
assembly with black holder,  
installation tape and pins.

#### FA10614\_LM1-M




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~25° medium beam optimized for  
CREE MC-E. 14.04 mm high  
assembly with installation tape.


### PRODUCTS:

#### CP19440\_LEILA-Y-SC2-M




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
~25° medium beam. Assembly with black SC2-holder.

#### FA11939\_LXM-M




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
~25° medium beam optimized for CREE XM-L. 14.8 mm high assembly with installation tape.

#### CP17587\_LEILA-SC-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
~9.6° spot beam

#### CA18978\_LEILA-Y-O-HLD2




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**  
~45° + 15° oval beam. 14.8 mm high assembly with black star-pcb holder, installation tape and pins.

#### CA11484\_LXP2-O-90



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**  
~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.  
Variant with beam direction rotated 90°.


#### LP20047\_LEILA-SC2-O-90-WAS-WHT



**Dimensions: mm x mm**  
**Height: mm**  
Asymmetric beam for wall-washing.  
Assembly with white SC2-holder.

### PRODUCTS:


#### CA14506\_G2-LXP2-RS2



**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~8.5° spot beam with light, black holder. Assembly with installation tape.

#### CA18485\_LEILA-Y-W-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**


~36° wide beam. 14.8 mm high assembly with white holder, installation tape and pins.

#### LE1-M

**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 15.10 mm**

~25° medium beam optimized for LedEngin LZ1(00XW00). 15.1 mm high assembly.


#### LP20038\_LEILA-SC2-WW



**Dimensions: mm x mm**  
**Height: mm**

~50° wide beam. Assembly with black SC2-holder.


#### CA12665\_LXB2-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.60 mm**

~14° diffused spot beam optimized for CREE XB-D. 14.6 mm high assembly with installation tape.

#### FA10661\_LXP-RS




**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

### PRODUCTS:


#### CP19454\_LEILA-Y-SC2-SS-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° smooth spot beam. Assembly with white SC2-holder.


#### CA12393\_LR2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.50 mm**

~40° wide beam optimized for LUXEON Rebel. 14.5 mm high assembly with installation tape.


#### CP17592\_LEILA-SC-O-WAS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

Asymmetric beam for wall-washing


#### CA18992\_LEILA-Y-WW-HLD2-WHT



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~55° wide beam. 14.8 mm high assembly with white star-pcb holder, installation tape and pins.


#### CA11929\_LR2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~9.6° spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

#### CA14511\_G2-LXP2-O-90-P




**Dimensions: 21.8 mm x 21.8 mm**  
**Height: 14.70 mm**

~10° x 40° oval beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape. Variant with beam direction rotated 90°. Variant with thin holder with pins.

### PRODUCTS:


#### CA18973\_LEILA-Y-SS-HLD2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° smooth spot beam. 14.8 mm high assembly with black star-pcb holder, installation tape and pins.


#### FA11450\_LXP-M2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.70 mm**

~30° medium beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.


#### LP20043\_LEILA-SC2-D-WHT



**Dimensions: mm x mm**  
**Height: mm**

~14° diffused spot beam. Assembly with white SC2-holder.


#### CP13059\_LOS-RS2



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~8.5° spot beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


#### FA10698\_LN2-REC



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 13.50 mm**

~35° x 25° rectangular beam optimized for Nichia NS6x83. 13.3 mm high assembly with installation tape.

#### LP20034\_LEILA-SC2-RS




**Dimensions: mm x mm**  
**Height: mm**

~9.6° spot beam. Assembly with black SC2-holder.

### PRODUCTS:


#### CP12414\_LOS-M



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~25° medium beam optimized for Osram Oslon Square EC. 14.3 mm high assembly.


#### CA18093\_LEILA-Y-WW



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~55° wide beam. 14.8 mm high assembly with black holder, installation tape and pins.


#### FA10650\_LM1-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.04 mm**

~14° diffused spot beam optimized for CREE MC-E. 14.04 mm high assembly with installation tape.


#### CP19441\_LEILA-Y-SC2-W



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~36° wide beam. Assembly with black SC2-holder.


#### CA12262\_LR2-RS



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.30 mm**

~9.6° spot beam optimized for LUXEON Rebel. 14.3 mm high assembly with installation tape.

#### CP17588\_LEILA-SC-D



**Dimensions: 21.6 mm x 21.6 mm**  
**Height: 14.80 mm**

~14° diffused spot beam

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)