

### PRODUCT FAMILY DATASHEET

### LINDA


Seamless linear extrusion lenses with excellent optical control and innovative installation.

LINDA is an industry first linear extrusion lens family with precise light control. The optics are made of diffused PMMA for high optical efficiency with good power and exceptional LED source hiding colour-over-angle performance for an extrusion. They are easy to install by either pressing or sliding the lens into the luminaire housing and are offered patterns. LINDA can in popular beam customized for luminaires for different lengths and is compatible with single row mid-power PCBs.



#### **PRODUCTS:**

### F17602\_LINDA-40-ZT25




Dimensions: 40.0 mm x 1140.0 mm

Height: 8.80 mm

Asymmetric beam for wall-washing

### F16860\_LINDA-UP




Dimensions: 25.7 mm x 1140.0 mm

Height: 7.80 mm

~145° + 100° extra wide beam for uplighting

### C18076\_LINDA-10-ZT25



Dimensions: 12.5 mm x 1140.0 mm

Height: 6.09 mm

Asymmetric beam for wall-washing


and shelf lighting



### PRODUCT FAMILY DATASHEET

### **PRODUCTS:**


### F17201\_LINDA-UP2



Dimensions: 25.4 mm x 1140.0 mm Height: 11.40 mm


~165° + 130° extra wide beam for uplighting

### F16748\_LINDA-O



Dimensions: 25.7 mm x 1140.0 mm Height: 4.98 mm

### F17603\_LINDA-40-Z2T25




Dimensions: 40.0 mm x 1140.0 mm

Height: 8.80 mm

Double assymetric beam for aisle and shelf lighting

### F17130\_LINDA-Z2T25-48in




Dimensions: 25.7 mm x 1220.0 mm

Height: 5.30 mm

Double asymmetric beam for aisle and shelf lighting. 48 inches in length.

### C18077\_LINDA-10-F

~40° + 100° oval beam




Dimensions: 12.5 mm x 1140.0 mm

Height: 5.59 mm

Asymmetric beam for undercabinet lighting

### F17599\_LINDA-40-WW



Dimensions: 40.0 mm x 1140.0 mm


Height: 8.80 mm ~90° + 110° wide beam



## PRODUCT FAMILY DATASHEET LINDA

### **PRODUCTS:**


### F16749\_LINDA-WW



Dimensions: 25.7 mm x 1140.0 mm Height: 5.30 mm

~70° + 100° beam


### C18073\_LINDA-10-O



Dimensions: 12.5 mm x 1140.0 mm Height: 7.17 mm

~35° + 85° oval beam

### F17131\_LINDA-ZT25-48in




Dimensions: 25.7 mm x 1220.0 mm

Height: 6.50 mm

Asymmetric beam for wall washing. 48 inches in length.

### C18078\_LINDA-10-UP




Dimensions: 12.5 mm x 1140.0 mm

Height: 10.26 mm

~145° + 100° extra wide beam for

uplighting

### F17600\_LINDA-40-W




**Dimensions: 40.0 mm x 1140.0 mm** 

Height: 8.80 mm

 $\sim$ 60° + 110° wide beam

### F16858\_LINDA-Z2T25



Dimensions: 25.7 mm x 1140.0 mm

Height: 5.30 mm

Double asymmetric beam for aisle


and shelf lighting



## PRODUCT FAMILY DATASHEET LINDA


### **PRODUCTS:**

### C18074\_LINDA-10-M




Dimensions: 12.5 mm x 1140.0 mm Height: 5.10 mm  $\sim$ 40° + 85° wide beam

### F17132\_LINDA-UP-48in




Height: 7.80 mm
~145° + 100° extra wide beam for uplighting. 48 inches in length.

### F16636\_LINDA-W60



Dimensions: 23.8 mm x 1140.0 mm Height: 6.34 mm ~60° + 90° beam


### F17601\_LINDA-40-O



Dimensions: 40.0 mm x 1140.0 mm Height: 8.80 mm

~86° + 40° oval beam

F16859\_LINDA-ZT25




Dimensions: 25.7 mm x 1140.0 mm

Height: 6.50 mm

Asymmetric beam for wall washing

C18075\_LINDA-10-W



Dimensions: 12.5 mm x 1140.0 mm

Height: 5.11 mm


~55° + 95° wide beam



# PRODUCT FAMILY DATASHEET LINDA

### **PRODUCTS:**


### F17194\_LINDA-WW2



Dimensions: 25.7 mm x 1140.0 mm

Height: 5.30 mm ~90° + 100° wide beam

### F16747\_LINDA-WWW



**Dimensions: 25.7 mm x 1140.0 mm** 

Height: 6.34 mm

~110° + 100° wide beam



## PRODUCT FAMILY DATASHEET

### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

### Local sales and technical support

www.ledil.com/ where\_to\_buy

### **Shipping locations**

Salo, Finland Hong Kong, China

### **Distribution Partners**

www.ledil.com/ where\_to\_buy