




L20118_OLGA-RS2




L20246_OLGA-SC2-HLD




Recommended PAD design



Clip reference distance after soldering



C18696_SOLDER-CLIP-2
Bottom of solder clip underneath holder
Opening of solder clip facing holder



LP20248_OLGA-SC2-RS2

COMPONENTS


INDEX	PART	TYPE	COUNT	MATERIAL	COLOR / COATING
1	L20118_OLGA-RS2	LENS	1	PMMA	CLEAR
2	L20246_OLGA-SC2-HLD	HOLDER	1	PC	BLACK

MECHANICAL DRAWING

PRODUCT
OLGA-SC2-RS2

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.
Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:



LEDiL

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 2:1

WEIGHT -

A3 SHEET 1 / 1

Notes

PCB or heatsink level.
LED location
Ensure LED fitting from a product specific 3D model available from www.ledil.com
For more details about installation please see LEDiL Installation Guide on www.ledil.com