


-  cut out dia. 4mm (Screw)
-  Led position
-  cut out dia. 3.2mm (Location pin)
-  Solder pad
-  cut out dia. 3mm (Assembly)

Typical pcb thickness is 1.6mm for Strada-IP and Hb-IP lens.

| PART               | TYPE | MATERIAL | COLOR / COATING |
|--------------------|------|----------|-----------------|
| For 2x6 Lens array |      |          |                 |

|   |  |   |
|---|--|---|
| <b>MECHANICAL DRAWING</b>   |  | <b>LEDiL</b>  |
| PRODUCT<br><b>PCB Layout 2x6</b>  |  |   |
| Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.<br>Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing. | FIRST ANGLE PROJECTION:<br> | This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy. |
| SCALE 1:1   | WEIGHT -   | A3 SHEET 1/1  |

**Notes**

Ensure LED fitting from a product specific 3D model available from [www.ledil.com](http://www.ledil.com)

For more details about installation please see LEDiL Installation Guide on [www.ledil.com](http://www.ledil.com)