

STRADA

The most versatile modular product family especially designed for street lighting, but also suitable for wide range of other applications

STRADA is LEDiL's most comprehensive product family with a wide variety of different beams suitable for both outdoor and indoor lighting. The standardized modules are available in 2X2 and 2X6 layouts as well as in two different single formats. 2X2MX features a standardized 90 x 90 mm footprint. The latest addition to the product family includes silicone versions for increased durability and thermal resistance. Being especially designed for street lighting they provide highly efficient and uniform lighting.


STRADA-2X2MXS

90 x 90 mm ingress protected 2X2 silicone arrays for up to 7070 size LED packages and 9 mm LES size COBs



PRODUCTS:


FP15812_STRADA-2X2MXS-VSM



Dimensions: 90.0 mm x 90.0 mm
Height: 13.00 mm

IESNA Type V (square) for wide areas lighting such as car parks. New revision.


FP15752_STRADA-2X2MXS-T3



Dimensions: 90.0 mm x 90.0 mm
Height: 14.83 mm

IESNA Type III (medium) beam for roads that are equal to or wider than mounting height.

FP15672_STRADA-2X2MXS-T4-B




Dimensions: 90.0 mm x 90.0 mm
Height: 14.20 mm

Wide IESNA Type IV forward-throw beam for wide area lighting like car parks.

PRODUCTS:

FP15589_STRADA-2X2MXS-T2




Dimensions: 90.0 mm x 90.0 mm

Height: 12.57 mm

IESNA Type II (medium) beam applicable
for European P-class standard
pedestrian lighting and M-class roads

FP14825_STRADA-2X2MXS-DWC2



Dimensions: 90.0 mm x 90.0 mm

Height: 14.40 mm

Universal road lighting beam with
excellent mixed illuminance and
luminance uniformity. Typically IESNA
Type II Medium.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)