

PRODUCT DATASHEET CP17596_TINA-SC-O

TINA-SC-O

~35° + 15° oval beam

SPECIFICATION:

Dimensions	Ø 16.2
Height	10.1 mm
Fastening	solder clip
ROHS compliant	yes 🛈




MATERIALS:

Component	Туре	Material	Colour	Finish	Length (mm)
TINA2-XP-O	Single lens	PMMA	clear		
TINA-SC-HLD	Holder	PC	black		

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP17596_TINA-SC-O	Single lens	2400	240	240	5.2
» Box size: 300 x 250 x 250 mm					

PRODUCT DATASHEET CP17596_TINA-SC-O




R

See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (SIMULATED):





OPTICAL RESULTS (SIMULATED):

LED XP-L2 40.0 + 22.0° / 72.0 + 47.0° FWHM / FWTM Efficiency 81 % Peak intensity 2.3 cd/lm LEDs/each optic 1 Light colour/type White Required components: Light distribution files OSRAM Opto Semiconductore OSLON Square CSSRM2/CSSRM3 I FD 40.0 + 18.0° / 66.0 + 35.0° FWHM / FWTM Efficiency 87 % Peak intensity 3.5 cd/lm LEDs/each optic 1 Light colour/type White Required components: Light distribution files SAMSUNG LED LM302D FWHM / FWTM 41.0 + 18.0° / 67.0 + 38.0° Efficiency 85 % Peak intensity 3 cd/lm LEDs/each optic 1 Light colour/type White Required components: Light distribution files



PRODUCT DATASHEET CP17596_TINA-SC-O

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

USA

Joensuunkatu 7 FI-24100 SALO Finland

LEDIL Inc. 228 West Page Street Suite D Sycamore IL 60178

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Poznan, Poland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy