

H

G

F

E


D

C


B

A


C11005_TINA2-XP-M




L20167_TINA-SC2-HLD






Recommended PAD design



Clip reference distance after soldering



C18696_SOLDER-CLIP-2

Bottom of solder clip underneath holder
Opening of solder clip facing holder

LP20185_TINA-SC2-M

COMPONENTS

INDEX	PART	TYPE	COUNT	MATERIAL	COLOR / COATING
1	C11005_TINA2-XP-M	LENS	1	PMMA	CLEAR
2	L20167_TINA-SC2-HLD	HOLDER	1	PC	BLACK

MECHANICAL DRAWING


PRODUCT

TINA-SC2-M

LEDiL

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing.
Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:



This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 3:1

WEIGHT -

A3 SHEET 1/1

Notes

- PCB or heatsink level.
- LED location
- Ensure LED fitting from a product specific 3D model available from www.ledil.com
- For more details about installation please see LEDiL Installation Guide on www.ledil.com