

WINNIE-O-C

~60° + 20° oval beam with holder C compatible with LEDiL HEKLA

SPECIFICATION:

Dimensions	Ø 50.0 mm
Height	19.5 mm
Fastening	socket
ROHS compliant	yes ⓘ



MATERIALS:


Component	Type	Material	Colour	Finish	Length
C14760_WINNIE-O	Single lens	PMMA	clear		49.6
C15821_WINNIE-HLD-C	Holder	PC	black		50.0

ORDERING INFORMATION:

Quantities for one set:

Single lens	1
Holder	1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C14760_WINNIE-O	Single lens	364	84	28	7.0
» Box size: 480 x 280 x 300 mm					
C15821_WINNIE-HLD-C	Holder	420		28	4.1
» Box size: 400 x 300 x 300 mm					





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):

bridgelux



LED V4 HD Gen 7
 FWHM / FWTM 62.0 + 16.0° / 77.0 + 40.0°
 Efficiency 83 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15253_HEKLA-SOCKET-A



Light distribution files

bridgelux



LED V6 Gen6
 FWHM / FWTM 64.0 + 18.0° / 79.0 + 43.0°
 Efficiency 82 %
 Peak intensity 1.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15253_HEKLA-SOCKET-A



Light distribution files

bridgelux

LED V6 HD Gen 7
 FWHM / FWTM 62.0 + 17.0° / 78.0 + 43.0°
 Efficiency 83 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C





Light distribution files

OPTICAL RESULTS (MEASURED):





LED V9 HD Gen7
FWHM / FWTM 60.0 + 19.0° / 79.0 + 48.0°
Efficiency 83 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files





LED VERO13
FWHM / FWTM 58.0 + 25.0° / 82.0 + 56.0°
Efficiency 81 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C16142_HEKLA-SOCKET-K



Light distribution files



LED VERO18
FWHM / FWTM 52.0 + 34.0° / 85.0 + 69.0°
Efficiency 79 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C16142_HEKLA-SOCKET-K





Light distribution files

OPTICAL RESULTS (MEASURED):





LED Vesta DTW 13mm (21W)
FWHM / FWTM 56.0 + 28.0° / 82.0 + 59.0°
Efficiency 79 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type Tunable White
Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 491 Typ L8



Light distribution files





LED Vesta TW 13mm (25W) CSP
FWHM / FWTM 57.0 + 26.0° / 81.0 + 57.0°
Efficiency 80 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 492 Typ L8



Light distribution files



LED Vesta TW 6mm DP
FWHM / FWTM 59.0 + 16.0° / 77.0 + 42.0°
Efficiency 80 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 504 Typ L8





Light distribution files

OPTICAL RESULTS (MEASURED):




LED Vesta TW 9mm (12W) CSP
 FWHM / FWTM 57.0 + 20.0° / 78.0 + 49.0°
 Efficiency 81 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K



Light distribution files

CITIZEN



LED CLC020 Series (Dim-To-Warm)
 FWHM / FWTM 58.0 + 20.0° / 78.0 + 49.0°
 Efficiency 81 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K



Light distribution files

CITIZEN

LED CLC030 Series (Dim-To-Warm)
 FWHM / FWTM 56.0 + 30.0° / 83.0 + 61.0°
 Efficiency 79 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K





Light distribution files

OPTICAL RESULTS (MEASURED):

CITIZEN



LED CLL02x/CLU02x (LES10)
 FWHM / FWTM 63.0 + 23.0° / 81.0 + 52.0°
 Efficiency 80 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files

CITIZEN



LED CLU700/701/702/703
 FWHM / FWTM 63.0 + 18.0° / 79.0 + 43.0°
 Efficiency 82 %
 Peak intensity 1.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files

CITIZEN

LED CLU7A2/7A3
 FWHM / FWTM 62.0 + 17.0° / 78.0 + 37.0°
 Efficiency 83 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C





Light distribution files

OPTICAL RESULTS (MEASURED):

CITIZEN



LED LCN-C01B (Tunable White)
 FWHM / FWTM 58.0 + 20.0° / 77.0 + 50.0°
 Efficiency 81 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 481 Typ L8



Light distribution files





LED CMT14xx
 FWHM / FWTM 61.0 + 22.0° / 81.0 + 52.0°
 Efficiency 83 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files



LED CMT19xx
 FWHM / FWTM 57.0 + 28.5° / 84.0 + 61.0°
 Efficiency 81 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I




Light distribution files

OPTICAL RESULTS (MEASURED):





LED CXA/B 13xx
 FWHM / FWTM 64.0 + 19.0° / 79.0 + 43.0°
 Efficiency 83 %
 Peak intensity 1.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15956_HEKLA-SOCKET-J



Light distribution files





LED LUXEON CX Plus CoB L08 (Gen2)
 FWHM / FWTM 56.0 + 28.0° / 83.0 + 61.0°
 Efficiency 82 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 637a Hekla



Light distribution files



LED LUXEON CoB 1202HD
 FWHM / FWTM 63.0 + 18.0° / 78.0 + 43.0°
 Efficiency 83 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15848_HEKLA-SOCKET-G





Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON CoB 1202s
FWHM / FWTM 64.0 + 18.0° / 79.0 + 43.0°
Efficiency 83 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15848_HEKLA-SOCKET-G



Light distribution files





LED LUXEON CoB 1204HD
FWHM / FWTM 61.0 + 21.0° / 80.0 + 49.0°
Efficiency 83 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15858_HEKLA-SOCKET-H



Light distribution files



LED LUXEON CoB 1205HD
FWHM / FWTM 59.0 + 24.0° / 81.0 + 54.0°
Efficiency 83 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15858_HEKLA-SOCKET-H





Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON CX Plus CoB - HD S01H4
FWHM / FWTM 61.0 + 16.0° / 77.0 + 40.0°
Efficiency 83 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 Bender Wirth: 634c Hekla



Light distribution files





LED LUXEON CX Plus CoB - HD S02H6
FWHM / FWTM 61.0 + 16.0° / 77.0 + 41.0°
Efficiency 83 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 Bender Wirth: 634c Hekla



Light distribution files



LED LUXEON CX Plus CoB - HD S04H9
FWHM / FWTM 60.0 + 20.0° / 80.0 + 50.0°
Efficiency 83 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 Bender Wirth: 634c Hekla




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON CX Plus CoB L04 / L05 (Gen2)
 FWHM / FWTM 58.0 + 23.0° / 81.0 + 54.0°
 Efficiency 82 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 637a Hekla



Light distribution files





LED LUXEON CX Plus CoB M02 / M03 (Gen2)
 FWHM / FWTM 58.0 + 19.0° / 78.0 + 48.0°
 Efficiency 83 %
 Peak intensity 1.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 641a Hekla



Light distribution files



LED LUXEON CX Plus CoB S01 (Gen2)
 FWHM / FWTM 60.0 + 16.0° / 77.0 + 40.0°
 Efficiency 83 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 Bender Wirth: 634c Hekla




Light distribution files

OPTICAL RESULTS (MEASURED):




LED LUXEON Fusion 12-up (20x24)
FWHM / FWTM 59.0 + 17.0° / 77.0 + 45.0°
Efficiency 82 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type Tunable White
Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 442 Typ L8



Light distribution files





LED CxM-14 (19x19)
FWHM / FWTM 58.0 + 29.0° / 84.0 + 60.0°
Efficiency 81 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files



LED CXM-4
FWHM / FWTM 62.0 + 16.0° / 78.0 + 39.0°
Efficiency 82 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15255_HEKLA-SOCKET-C





Light distribution files

OPTICAL RESULTS (MEASURED):





LED CxM-9 (13.5x13.5)
FWHM / FWTM 62.0 + 23.0° / 81.0 + 52.0°
Efficiency 82 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files




LED Fortimo SLM L09 CoB
FWHM / FWTM 60.0 + 20.0° / 80.0 + 50.0°
Efficiency 83 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 F15858_HEKLA-SOCKET-H



Light distribution files



LED Fortimo SLM L13 CoB
FWHM / FWTM 27.0 + 55.0° / 58.0 + 81.0°
Efficiency 81 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
 C16142_HEKLA-SOCKET-K
 Bender Wirth: 432 Typ L8





Light distribution files

OPTICAL RESULTS (MEASURED):

PHILIPS



LED Fortimo SLM L15 CoB
FWHM / FWTM 54.0 + 30.0° / 83.0 + 63.0°
Efficiency 80 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
C16142_HEKLA-SOCKET-K
Bender Wirth: 432 Typ L8



Light distribution files

SAMSUNG



LED LC003D / LC006D / LC009D / LC013D
FWHM / FWTM 62.0 + 22.0° / 81.0 + 51.0°
Efficiency 82 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files

SAMSUNG

LED LC010C
FWHM / FWTM 65.0 + 20.0° / 80.0 + 46.0°
Efficiency 81 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15848_HEKLA-SOCKET-G





Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG



LED LC010C G2
 FWHM / FWTM 62.0 + 17.0° / 78.0 + 41.0°
 Efficiency 82 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C



Light distribution files

SAMSUNG



LED LC016D / LC019D / LC026D / LC033D
 FWHM / FWTM 58.0 + 29.0° / 85.0 + 62.0°
 Efficiency 80 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files

SAMSUNG

LED LC020C
 FWHM / FWTM 63.0 + 21.0° / 81.0 + 48.0°
 Efficiency 82 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15848_HEKLA-SOCKET-G





Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG



LED LC020C G2
FWHM / FWTM 61.0 + 20.0° / 81.0 + 47.0°
Efficiency 82 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15859_HEKLA-SOCKET-I



Light distribution files

TRIDONIC



LED SLE G7 LES09
FWHM / FWTM 62.0 + 21.0° / 81.0 + 49.0°
Efficiency 82 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files

TRIDONIC

LED SLE G7 LES13
FWHM / FWTM 59.0 + 27.0° / 83.0 + 58.0°
Efficiency 80 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15859_HEKLA-SOCKET-I





Light distribution files

OPTICAL RESULTS (MEASURED):

TRIDONIC



LED SLE G7 LES15
 FWHM / FWTM 58.0 + 29.0° / 85.0 + 62.0°
 Efficiency 80 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files

XICATO


LED XOB 14.5 mm
 FWHM / FWTM 58.0 + 29.0° / 84.0 + 61.0°
 Efficiency 80 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files

XICATO

LED XOB 9.8 mm
 FWHM / FWTM 62.0 + 22.0° / 81.0 + 51.0°
 Efficiency 82 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15255_HEKLA-SOCKET-C




Light distribution files

OPTICAL RESULTS (SIMULATED):

bridgelux


LED V13 Gen 8-9
FWHM / FWTM 58.0 + 27.0° / 83.0 + 58.0°
Efficiency 79 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17438_HEKLA-G2-I



Light distribution files

bridgelux


LED V13 Gen 8-9
FWHM / FWTM 58.0 + 27.0° / 83.0 + 58.0°
Efficiency 81 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F17438_HEKLA-G2-I



Light distribution files

bridgelux

LED VERO10
FWHM / FWTM 59.0 + 18.0° / 78.0 + 45.0°
Efficiency 83 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15616_HEKLA-SOCKET-F




Light distribution files

OPTICAL RESULTS (SIMULATED):

CITIZEN


LED CLL03x/CLU03x
 FWHM / FWTM 58.0 + 26.0° / 82.0 + 57.0°
 Efficiency 77 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files

CITIZEN


LED CLU710/711
 FWHM / FWTM 61.0 + 18.0° / 78.0 + 42.0°
 Efficiency 83 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15859_HEKLA-SOCKET-I



Light distribution files



LED CXA/B 15xx
 FWHM / FWTM 59.0 + 17.0° / 79.0 + 42.0°
 Efficiency 84 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15256_HEKLA-SOCKET-D




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED CXA/B 1816 & CXA/B 1820 & CXA 1850
 FWHM / FWTM 56.0 + 13.0° / 75.0 + 35.0°
 Efficiency 86 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15254_HEKLA-SOCKET-B



Light distribution files



LED CXA/B 1830
 FWHM / FWTM 60.0 + 28.0° / 84.0 + 60.0°
 Efficiency 79 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 C16142_HEKLA-SOCKET-K




Bender Wirth: 457 Typ L8

Light distribution files



LED XP-G3
 FWHM / FWTM 58.0 + 14.0° / 76.0 + 32.0°
 Efficiency 84 %
 Peak intensity 2.4 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F17438_HEKLA-G2-I




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED COB T-Type
 FWHM / FWTM 62.0 + 18.0° / 78.0 + 38.0°
 Efficiency 83 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F15848_HEKLA-SOCKET-G



Light distribution files




LED NFSWE11A
 FWHM / FWTM 58.0 + 18.0° / 76.0 + 42.0°
 Efficiency 74 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 30
 Light colour/type White
 Required components:



Light distribution files



LED OSOLON Square CSSRM2/CSSRM3
 FWHM / FWTM 58.0 + 14.0° / 74.0 + 30.0°
 Efficiency 86 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:
 F17438_HEKLA-G2-I




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED Soleriq S13 19x19
FWHM / FWTM 57.0 + 24.0° / 81.0 + 54.0°
Efficiency 83 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15859_HEKLA-SOCKET-I



Light distribution files

OSRAM
Opto Semiconductors


LED Soleriq S9
FWHM / FWTM 59.0 + 20.0° / 80.0 + 48.0°
Efficiency 85 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15255_HEKLA-SOCKET-C



Light distribution files



SEUL
SEOUL SEMICONDUCTOR

LED MJT COB LES 14.5
FWHM / FWTM 58.0 + 30.0° / 84.0 + 62.0°
Efficiency 80 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:
F15859_HEKLA-SOCKET-I



Light distribution files

OPTICAL RESULTS (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)