

PRODUCT RELEASE

STRADA-IP-2X6-T2-B & T3-B – Type II/III (Medium) street lighting improved

LEDiL proudly presents the new 2X6 module designed for the IESNA Type 2 and 3 street lighting. These new "-B" versions are revised from the well known -T2 and -T3 designs, maintaining close to identical beam performance and functionality, but with reduced house-side spill light. These "facelift" versions are especially recommended for new designs, but can be quickly adapted into earlier designs bringing the performance close to perfection. Both versions include an integrated silicone gasket to allow IP67 rated luminaires.

- » Identical beam to well known -T2 and -T3 designs with minimized spill light to house side & better availability
- » Easy to achieve full cutoff luminaire designs with no direct uplight and controlled glare
- » IESNA Type II/III beams (also suitable for European ME & S classes) with excellent performance, uniformity and durability (IP67)

FEATURES

- Wide square-shaped beam pattern
- Well established 2X6 module based structure
- Integrated silicone gasket for IP67 rated products

TYPICAL APPLICATIONS

- Roads and streets
- Wide outdoor areas

The information contained herein is the property of LEDiL Oy, Salorankatu 10, FI-24240 SALO, Finland and is subject to change without notice. Please visit www.ledil.com for additional information, such as the latest photometric files, 3D mechanical models, and application notes relating to handling, gluing and taping.



TECHNICAL SPECIFICATIONS

- Dimensions: 71,4 x 173 mm
- LEDs: 12
- Mounts with screws
- Precision-molded from optical grade PMMA – UL94 HB rated material with operating rating -40°C to +80°C

COMPATIBILITY


• Optimized for a range of 3535 high power and compatible up to 5050 LED packages

	OLD T2	NEW T2-B	OLD T3	NEW T3-B
E _{av} (lx)	11	12	12	12
u0	0.524	0.563	0.450	0.433

Simulated results based on same setup.



- Height: 12.75
- Dimensions: 71.4 x 173 mm
- Typical efficiency: 95%
- Typical FWHM: Asymmetric
- IESNA Type III beam distribution




OLD T2



NEW T2-B

STRADA-IP-2X6-T2-B

- Height: 12.03 mm
- Dimensions: 71.4 x 173 mm
- Typical efficiency: 95%
- Typical FWHM: Asymmetric
- IESNA Type II beam distribution





ORDERING INFORMATION

CS15363_STRADA-IP-2X6-T2-B CS15362_STRADA-IP-2X6-T3-B

Visit www.ledil.com for ordering codes and latest product specifications, which may vary by LED

The information contained herein is the property of LEDiL Oy, Salorankatu 10, FI-24240 SALO, Finland and is subject to change without notice. Please visit www.ledil.com for additional information, such as the latest photometric files, 3D mechanical models, and application notes relating to handling, gluing and taping.