

STRADA-IP-2X6

Standardized 2X6 modules with integrated silicone gasket

STRADA-IP-2X6 are IP66 and IP67 tested lens modules with wide range of highly efficient street lighting beams. The integrated silicone gasket ensures ingress protection against water and dust allowing them to be used without protective covers. The lens modules are mounted with 8 screws and have enough reserved space to fit in needed luminaire components.



NEW

STRADA-IP-2X6-T2-B-90 and -T3-B-90

IESNA Type II and III street light optics with 90° rotated beams

FEATURES

- LEDiL standard 2X6 footprint with integrated silicone seal
- Wide square-shaped beam pattern turned 90-degrees
- Up to IP67 and designed to be used without protective glass
- Fastening with 8 screws
- Space reserved inside for PCB screws, connectors, wires and other components
- Available in PMMA
- Dimensions: 173 x71,4 mm

TYPICAL APPLICATIONS

- Street lighting
- Wide outdoor areas




STRADA-IP-2X6-T2-B-90



STRADA-IP-2X6-T3-B-90


COMPATIBILITY

- Up to 5050 size LED packages




STRADA-IP-2X6-DWC

D: 173 x 71,4 mm
H: 7,9 mm
Typ. efficiency: 93%




STRADA-IP-2X6-ME

D: 173 x 71,4 mm
H: 8,4 mm
Typ. efficiency: 94%



STRADA-IP-2X6-VSM

D: 173 x 71,4 mm
H: 9 mm
Typ. efficiency: 94%




STRADA-IP-2X6-T2-B

D: 173 x 71,4 mm
H: 12,03 mm
Typ. efficiency: 95%




STRADA-IP-2X6-T3-B

D: 173 x 71,4 mm
H: 12,75 mm
Typ. efficiency: 94%




STRADA-IP-2X6-T4-B

D: 173 x 71,4 mm
H: 10,57 mm




STRADA-IP-2X6-SCL

D: 173 x 71,4 mm
H: 9,6 mm
Typ. efficiency: 94%




STRADA-IP-2X6-FW

D: 173 x 71,4 mm
H: 13,1 mm



NEW
STRADA-IP-2X6-T2-B-90

D: 173 x 71,4 mm
H: 12,03 mm



NEW
STRADA-IP-2X6-T3-B-90

D: 173 x 71,4 mm
H: 12,75 mm

ORDERING INFORMATION

Consult www.ledil.com/strada-ip-2x6 for ordering codes and latest product specifications, which may vary by LED.