LINNEA

40 mm wide linear lens family for mid-power PCBs

LINNEA is a low profile linear design family (285 x 40 x 9.7 mm) that allows lenses to be attached seamlessly together and fitted into many existing luminaire designs. It provides high quality indoor lighting with reduced glare. Fastening the optic with integrated clips and dedicated snap-on end part accessories makes the whole installation process quck and easy. The family consists of a variety of symmetrical and asymmetrical beams and is optimized for the most common Zhaga mid-power 20 and 24 mm wide PCBs.



NEW

LINNEA-UP

A uniform ceiling light that not only makes the space cosy and bright but also helps to reduce glare in offices and other indoor spaces.


FEATURES

- 280 x 40 mm linear lens with low profile
- Very wide sideway throwing light spread for uplighting
- Durable design made from PC
- Quick to assemble with integrated clips
- End cap accessories available

TYPICAL APPLICATIONS


- Office lighting
- Architectural lighting
- Retail lighting

DESIGN EXAMPLE




LINNEA-UP

LED module: LM561B+ Luminous flux (LED module): 650 lm



FLORENCE2-Z90

LED module: Fortimo LED Line 1ft 650 lm 840 3E LV3 Luminous flux (LED module): 650 lm




RESULTS AT 0.85 M HEIGHT:

Average LUX: 621 lx Min LUX: 199 lx Max LUX: 835 lx U_o: 0.32 UGR: Max 17


LEDIL

COMPATIBILITY


- Zhaga book 7 and similar mid-power 20 mm and 24 mm wide PCBs
- Recommended PCB design files available
- Simple snap installation for 1.0 mm thick and B-variants for 0.5 mm thick surfaces




F16048_LINNEA-UP




F15524_LINNEA-60 F15941_LINNEA-60-B




F15523_LINNEA-90 F15940_LINNEA-90-B



F15756_LINNEA-O F15952_LINNEA-O-B



F15861_LINNEA-ZT25 F16000_LINNEA-ZT25-B



F15860_LINNEA-Z2T25 F15999_LINNEA-Z2T25-B

ORDERING INFORMATION

Consult www.ledil.com/linnea for ordering codes and latest product specifications, which may vary by LED.