

STRADA-IP-2X6

Standardized 2X6 modules with integrated silicone gasket

STRADA-IP-2X6 family consists of 173 x 71,4 mm lens modules with a wide range of highly efficient street lighting beams. Up to IP67 lenses with an integrated silicone gasket ensure ingress protection against water and dust allowing them to be used without protective covers. The lens modules are mounted with 8 screws and have enough space for luminaire components.

NEW

STRADA-IP-2X6-DWC-B

Original -DWC now with same mechanical features as the rest of the STRADA-IP-2X6 family

FEATURES

- Updated mechanics including screw holes and component pockets
- Silicone sealed wide asymmetric street light array with up to IP67 ingress protection
- Ideal installation ratio 1:1 to road width and mounting height

TYPICAL APPLICATIONS

- Universal street lighting
- European M/ME classes
- IESNA Type III (cutoff/full cutoff)



COMPATIBILITY

- Up to 5050 size LED packages




STRADA-IP-2X6-DWC-B

D: 173 x 71,4 mm

H: 8,9 mm

Typ. efficiency: 94%




STRADA-

IP-2X6-DWC

D: 173 x 71,4 mm

H: 7,9 mm

Typ. efficiency: 93%




STRADA-

IP-2X6-ME

D: 173 x 71,4 mm

H: 8,4 mm

Typ. efficiency: 94%




STRADA-

IP-2X6-VSM

D: 173 x 71,4 mm

H: 9 mm

Typ. efficiency: 94%




STRADA-

IP-2X6-SCL

D: 173 x 71,4 mm

H: 9,6 mm

Typ. efficiency: 94%




STRADA-

IP-2X6-FW

D: 173 x 71,4 mm

H: 13,1 mm




STRADA-

IP-2X6-T2-B

D: 173 x 71,4 mm

H: 12,03 mm

Typ. efficiency: 95%




STRADA-IP-

2X6-T2-B-90

D: 173 x 71,4 mm

H: 12,03 mm




STRADA-

IP-2X6-T3-B

D: 173 x 71,4 mm

H: 12,75 mm

Typ. efficiency: 94%




STRADA-IP-

2X6-T3-B-90

D: 173 x 71,4 mm

H: 12,75 mm



STRADA-

IP-2X6-T4-B

D: 173 x 71,4 mm

H: 10,57 mm

ORDERING INFORMATION

Consult www.ledil.com/strada-ip-2x6 for ordering codes and latest product specifications, which may vary by LED.